

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in
LUCE

(County)	Located In:	Corner Code #/
1. Public Land Survey	T _____ R _____	_____
	T _____ R _____	_____
	T _____ R _____	_____
	T _____ R _____	_____
2. Property Controlling in Section	S <u>33</u> T <u>47N</u> R <u>10W</u>	<u>12</u>
	S <u>33</u> T <u>47N</u> R <u>10W</u>	<u>11</u>
	S <u>33</u> T <u>47N</u> R <u>10W</u>	<u>15</u>
3. Miscellaneous Property in Sec.	S _____ T _____ R _____	_____

Register of Deeds Stamp & File Number

4. Lot No. _____, Recorded Plat _____
 5. Private Claims _____

I, Stephan J. Szyszkoski, in a field survey on September 06, 1994, 19_____, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law, established, re-established, monumented, re-monumented, recovered, found as expressed below.

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

	A	B	C	D	E	F	G	H	I	J	K	L	M
2	6	5	4	3	2	1							
3													
4	7	8	9	10	11	12							
5													
6	13	14	15	16	17	18							
7													
8	19	20	21	22	23	24							
9													
10	25	26	27	28	29	30							
11													
12	31	32	33	34	35	36							
13													

A. Description of original monument and accessories and/or subsequent restoration:

- (12-Sec. 33) South 1/16 corner, Section 33. Corner not established in the original survey. Found no subsequent record.
 (11-Sec. 33) Southwest 1/16 corner, Section 33. Corner not established in the original survey. Found no subsequent record.
 (15-Sec. 33) West 1/16 between Section 33 T47N-R10W and Section 4 T46N-R10W. Corner not established in the original survey. Found no subsequent record.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

- (12-Sec. 33) Found no evidence of prior monumentation at the corner position. Established the corner midway and on a straight line between 1/4 corner 1307.57' south and center of section 1307.57' north. The center is an unmonumented position, being the intersection of straight lines connecting opposite quarter corners. At the position for the corner, I placed a 1" I.D.x36' iron pipe capped with a 4" dia. cast aluminum MDNR tablet, appropriately stamped.
 (11-Sec. 33) Found no evidence of prior monumentation at the corner position. Established the corner at the intersection of straight lines connecting opposite 1/16 corners, the 1/16s South and East being monumented, those North and West being unmonumented computed positions midway and on straight lines between repetitive section/quarter corners. At the position for the corner, I placed a 1" I.D.x36' iron pipe capped with a 4" dia. cast aluminum MDNR tablet, appropriately stamped.
 (15-Sec. 33) Found no evidence of prior monumentation at the corner position. Established the corner midway and on a straight line between Section corner 1320.33' west and quarter corner 1320.33' east. Recovered a "t" iron survey marker, 30.97' north of the corner, and 0.98' east of the 1/16 line. At the position for the corner I placed a 1" I.D.x36' iron pipe capped with a 4" dia. cast aluminum MDNR tablet, appropriately stamped.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

- | | | |
|---|--|---|
| (12) Set 1" iron pipe with MDNR cap.
Blazed, scribed, and placed measuring nails with tags in the following bearing trees:
6" Tamarack S80E 12.5' "S1/16 BT"
5" Spruce S22W 6.55' "S1/16 BT"
14" W. Pine S63N 43.6' "S1/16 BT"
10" Tamarack N56N 10.2' "S1/16 BT"
Placed a 4" tamarack post adjacent.
Bearings are magnetic. | (11) Set 1" iron pipe with 4" MDNR cap.
Blazed, scribed, and set measuring nails with tags in the following bearing trees:
6" Tamarack S04E 60.5' "SW1/16 BT"
14" W. Pine S23E 82.9' "SW1/16 BT"
10" Tamarack S43E 47.4' "SW1/16 BT"
5" Tamarack N80E 47.7' "SW1/16 BT"
Placed a 5" squared tamarack post adjacent. Bearings are magnetic. | (15) Set 1" iron pipe with 4" MDNR cap.
Blazed, scribed, and set measuring nails in the following bearing trees:
12" Maple S24W 9.6' "W1/16 BT"
5" Maple S64W 36.4' "W1/16 BT"
5" W. Birch North 47.25' "W1/16 BT"
Fd. "t" iron N08E 31.0'
Placed a 6" squared cedar post adjacent.
Bearings are magnetic. |
|---|--|---|

Signed by Stephan J. Szyszkoski Date 10-17-94

Surveyor's Michigan License No. 33986

FORM APPROVED BY MICHIGAN STATE LAND SURVEYORS ASSOCIATION
 For the Michigan Department of Natural Resources - Forest Management Division

