## LAND CORNER RECORDATION CERTIFICATE

## FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

Luce Co.

Form No. ML M735
DOUBLEDAY BROS. B. CO., KALAMAZOO, MICH.

FOR CORNERS OF -:	LOCATED IN -:	CORNER CODE NUMBER	
1. PUBLIC LAND SURVEY	T. 45 K, R. 9	H-11	-
2. PROPERTY CONTROLL- ING IN SECTION	,T N. R E		_
3. MISCELLANEOUS PROPERTY IN SECTION		:	-
6. LOT NO , RECO			
5. PRIVATE CLAIMS			REGISTER OF DEEDS STAMP AND
			FILING NUMBER
the corner points mentioned in field survey on	lines 1 and 2 above (id /319_72, established in conformance with re- nited States Department of that the corner points found, recovered, restored	entified with circles on inde- ed, re-established, monumer gulations and rules therefore of the Interior, Bureau of Lan- mentioned in lines 3,4 and , established or re-established	of P.A.74, Michigan P.A. of 1970, ex code diagram – over) were, in a steed, re-monumented, recovered or as required in the current manual ad Management or by a decree of a 5 above were, in a field survey on a das expressed below and in convoca or, by a Decree of a Court of
A. Description of original monu	ument and accessories an	d/or subsequent restoration:	
E-11 4 Cor. bet. Se	ecs. 27-34.		
B. Description of corner eviden	nce found and/or method s	applied in restoring or re-est	ablishing corner:
H-11 Found 6" concr		y Luce Co. Road Commi	-
H-11 Found 6" concr	rete post, placed by	y Luce Co. Road Commi	-
E-11 Found 6" concr Beech, S3 <sup>0</sup> E, 9	rete post, placed b 9.0', Tree Scribed	y Luce Co. Road Commi.	ssion, with a 30"
E-11 Found 6" concr Beech, S3 <sup>0</sup> E, 9	rete post, placed by	y Luce Co. Road Commi.	-
E-11 Found 6" concrement for Beech, S3°E, 9  C. Description of monument for H-11 Re-witnessed Concrement for Bearings:	rete post, placed by	y Luce Co. Road Commi.	ssion, with a 30"
E-11 Found 6" concrement for Beech, S3°E, 9  C. Description of monument for H-11 Re-witnessed Concrement for Bearings:	rete post, placed by 9.0', Tree Scribed or corner and accessories Corner	y Luce Co. Road Commi.	ssion, with a 30"
E-11 Found 6" coner Beech, 83°E, 9  C. Description of monument for H-11 Re-witnessed 0 New Bearings: 2  Corner lies 39	rete post, placed by 9.01, Tree Scribed or corner and accessories Corner R4" Hemlock S49°E P.21 East of Center	y Luce Co. Road Commi.	ssion, with a 30"
E-11 Found 6" concrement, 53°E, 9  C. Description of monument for H-11 Re-witnessed Gally & Corner lies 39	Tete post, placed by 1.0', Tree Scribed or corner and accessories Corner R4" Hemlock S49°E P.2' East of Center	y Luce Co. Road Commi.	ecating the position of the corner:
E-11 Found 6" concressed of the Bearings:  Corner lies 39  Gally Concressed of the Bearings:  Corner lies 39	rete post, placed by 9.0', Tree Scribed or corner and accessories Corner R4" Hemlock S49°E P.2' East of Center Puckles	Luce Co. Road Comminus established to perpetuate lo 33.91 Line M-123.	ecating the position of the corner:
E-11 Found 6" coner Beech, 53°E, 9  C. Description of monument for H-11 Re-witnessed Conner lies 39  Corner lies 39  Gilly Congress Michigan Regulary Engress Michigan Regulary English Programme Prog	rete post, placed by 1.0', Tree Scribed or corner and accessories Corner  24" Hemlock S49°E  2.2' East of Center  D. Buckler  ISTRATION NO.	Luce Co. Road Comminus established to perpetuate lo 33.91 Line M-123.	exacting the position of the corner:
E-11 Found 6" coner Beech, S3°E, 9  C. Description of monument for H-11 Re-witnessed Conner lies 39  Corner lies 39  SIGNED BY Brilly I SURVEYOR'S MICHIGAN REG	rete post, placed by 9.0', Tree Scribed or corner and accessories Corner 24" Hemlock S49°E 9.2' East of Center 9.2' East of Center 15 Ruckler 15 ISTRATION NO	Line M-123.  DATE  8887	exacting the position of the corner:
C. Description of monument for H-11 Re-witnessed Onew Bearings:  Corner lies 39  SIGNED BY Brily I SURVEYOR'S MICHIGAN REG	rete post, placed by 9.0', Tree Scribed or corner and accessories Corner  24" Hemlock S49°E  9.2' East of Center  9.2' East of Center  1 Suckler  1 ISTRATION NO  ATES AGENCIES:	Line M-123.  DATE  B887	exacting the position of the corner:

FORM APPROVED BY MICHIGAN STATE BOARD OF REGISTRATION, JAN. 28, 1971 DISTRIBUTED BY MICHIGAN SOCIETY OF REGISTERED LAND SURVEYORS