File Livingston 6 Section 6

LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF—:	LOCATED IN—:	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY _____	T. _____ N. S., R. _____ E. W.	_____
2. PROPERTY CONTROLLING IN SECTION 11	,T. 1 N. S., R. 5 E. W.	I-3, I-4
3. MISCELLANEOUS PROPERTY IN SECTION 11	,T. 1 N. S., R. 5 E. W.	1, 3
4. LOT NO. _____ , RECORDED PLAT _____		
5. PRIVATE CLAIMS _____		

REGISTER OF DEEDS STAMP AND FILING NUMBER

I, Dwayne Scott do hereby certify that under requirements of P.A.74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above (identified with circles on index code diagram – over) were, in a field survey on October 1975, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on October 1975, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

A. Description of original monument and accessories and/or subsequent restoration:

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

I-3 3/4" Iron Pipe

1 - North 1/8 Cor. N.W. ¼
Rec. Old Post with Stones around it.
Set. ½" Iron Pipe
Rec. with Witnesses from Munsell & Garlock
Dated 1921

I-4 Set. 3/4" Iron Pipe
Set. from Munsell & Garlock
Witness Dated 1909

3 - West 1/8 Cor. of N.W. ¼
Set. ½" Pipe
Single Proportion Dist.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

I-3 3/4 Iron Pipe
N. 49° E. 21.30' 30" B. Oak P.K. & Tag
S. 80° W. 60.50' 8" Hickory P.K. & Tag
S. 20° E. 73.05' Twin 8"&12" B. Oaks P.K. & Tag.

1 -North 1/8 Cor. N.W.¼
½" Iron Pipe
S.86° E. 69.78' 18" B.Oak P.K.& Tag
South 9.59' Twin 12" Oaks P.K.& Tag
N.10° E. 32.35' Twin 14'B. Oaks P.K. & Tag

I-4 3/4" Iron Pipe
South 24.35' 17" W. Oak P.K. & Tag
N.75° W. 23.97' 22" W. Oak P.K. & Tag
N.02° E. 15.83' 13" B. Oak P.K. & Tag

3 - West 1/8 Cor. N.W. ¼
N.50° E. 26.39' B. Oak Spike & Tag
S.31° E. 42.41' 13" Hickory P.K. &Tag
N.88° W. 22.10' 19" B. Oak P.K. & Tag

SIGNED BY _____ DATE _____

SURVEYOR'S MICHIGAN REGISTRATION NO. _____ (SEAL)

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY _____ DATE _____

APPROVED AND SIGNED BY _____ (CHIEF OF SURVEY PARTY / MICHIGAN REGISTERED LAND SURVEYOR) DATE Dec 1975 (SEAL)

PAGE 11

SURVEYOR'S MICHIGAN REGISTRATION NO. 12029

Form No. MLM 735 [illegible]

FORM APPROVED BY MICHIGAN STATE BOARD OF [illegible] 29 [illegible]
DISTRIBUTED BY MICHIGAN SOCIETY OF [illegible]