LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF -:	LOCATE		CORNER CODE NUMBER	
1. PUBLIC LAND SURVEY.	24 T. 4	. Å., R. ¥¥	K-7, M-9	
2. PROPERTY CONTROLL- ING IN SECTION	T	N. E. E. S., R W.		
3. MISCELLANEOUS PROPERTY IN SECTION	,Т	S., R E.		
4, LOT NO , RI	ECORDED PLA	NT		
5. PRIVATE CLAIMS				REGISTER OF DEEDS STAMP AND FILING NUMBER
the corner points mentioned field survey on Noverestored as expressed below of survey instructions of the court of law. Furthermore 19.	d in lines 1 a 19 w and in confee United State ore, that the , found, reco	and 2 above (ider of, established ormance with regu es Department of corner points m overed, restored, e	itified with circles on index l, re-established, monumente lations and rules therefore a the Interior, Bureau of Land entioned in lines 3,4 and 5 established or re-established	P.A. 74, Michigan P.A. of 1970, code diagram – over) were, in a ed, re-monumented, recovered or as required in the current manual Management or by a decree of a above were, in a field survey on as expressed below and in contrast or, by a Decree of a Court of
A. Description of original n	monument and	accessories and/	or subsequent restoration:	
		and/or method ap	plied in restoring or re-estab	olishing corner:
7 Found 1/2 Iron word Record Boss Eng.	Rod led by of	m-	9 Found 4" D. Cap. Corner was	in Brass Reset by W. Paddison P.L. Benton Recovere
7 Found 1/2 Iron Corner Record Boss Eng. Howell Recorded With C. Description of monumen	Rod led by of of ave in 'C' nt for corner	<i>M-</i>	9 Found 4" D. Cap. Corner was D.N.R. Surveyor, the Corner and IN Howell established to perpetuate loc	Pin Brass Reset by W. Paddison P.L. Benton Recovered Recovered Accorded it
7 Found 1/2 Iron Corner Record Boss ENG. Howell Recorded With	Rod led by of evering Control of for corner of 48 "OAK	and accessories and Sp. W.Side	9 Found 4" Din Cap. Corner was D.N.R. Surveyor. And IN Howell established to perpetuate loc M-9 4" Din S.70°W. S.80°E. 6	Reset by L. Paddison Recovered Recovered Recovered Recovered Accorded it tating the position of the corner: Bross Plug (Cap) 13.79' PP Sp. W. Side 48.58' S.E. Cor. Barn 36.58' M.B.T. Pole Sp. N. Side
Trond 1/2 Tron Corner Record Boss Eng. Howell Recorded Wif A C. Description of monumer 7 1/2 "Tron Rod S. 25° E. 5.41" 5 69° W 49.50	Rod led by of vein'C' nt for corner 48 "On 40"Onk Southerh	and accessories and Sp. W.Side	9 Found 4" Din Cap. Corner was D.N.R. Surveyor. And IN Howell established to perpetuate loc M-9 4" Din S.70°W. S.80°E. 6	Reset by No. Padd ison Recovered Recovered Recovered Recovered It tating the position of the corner: Bross Plus (cap) 13.79' PPSp. W. Side 48.58' S.E.Cor, Barn 86.58' M.B.T. Pole Sp.
Trond 1/2 Tron Corner Record Boss Eng. Howell Recorded Wif A C. Description of monumer 7 1/2 "Tron Rod S. 25° E. 5.41" S 69° W 49.50 N. 75° W. 9.68	Rod led by of ave in 'C' nt for corner of 48 "On Southerh s wit.)	and accessories of the sp. W.S.de of Sp. N. Side of End C.M.F.	9 Found 4" Din Cap. Corner was D.N.R. Surveyor. And IN Howell established to perpetuate loc M-9 4" Din S.70°W. S.80°E. 6	Reset by M. Padd ison Reset by M. Padd ison Recovered Recovered
Pound 1/2 Tron Corner Record Boss Eng. Howell Recorded Wif A C. Description of monumer 7 1/2 "Tron Rod S. 25° E. 5.41" S 69° W 49.50 N. 75° W. 9.68 (Boss Eng	Rod Led by of ave in 'C' nt for corner of 48 "On Southerh wit.) Novan	and accessories accessories and accessories and accessories are accessories and accessories accessories and accessories accessories and accessories accessories accessories and accessories accessorie	P. Found 4" L. Cap. Corner was D.N.R. Surveyor the Corner and IN Howell established to perpetuate loc M-9 4" Din S.70°W. N.60°W. S.80°E. & (P.L. Be	Reset by M. Padd ison Reset by M. Padd ison Recovered Recovered
Pound 1/2 Tron Corner Record Boss Eng. Howell Recorded Wif A C. Description of monumer 7 1/2 "Tron Rod S. 25° E. 5.41" S 69° W 49.50 N. 75° W. 9.68 (Boss Eng. SIGNED BY. Tom	Rod led by of ave in 'C' not for corner " 48 "OAK Southerly " Wit.) Notan REGISTRATI	and accessories and Sp. W.Side Sp. N. Side End C.M.F. ON NO.	P. Found 4" L. Cap. Corner was D.N.R. Surveyor the Corner and IN Howell established to perpetuate loc M-9 4" Din S.70°W. N.60°W. S.80°E. & (P.L. Be	Reset by W. Padd ison Reset by W. Padd ison Recovered Recovered
Trond 1/2 Tron Corner Record Boss Eng. Howell Recorded Wif A C. Description of monumer 7 1/2 Tron Rod S. 25° E. 5.41 S 69° W 49.50 N. 75° W. 9.68 Boss Eng SIGNED BY. Tom SURVEYOR'S MICHIGAN I	Rod led by of ave in 'C' nt for corner of 40"OAK Southerh Southerh REGISTRATE OSTATES AG	and accessories Ak Sp. W.Side K Sp. N. Side M. End C.M.F. ON NO ENCIES:	P. Found 4" L. Cap. Corner was D.N.R. Surveyor the Corner and IN Howell established to perpetuate loc M-9 4" Din S.70°W. N.60°W. S.80°E. & (P.L. Be	Reset by M. Paddison Recovered Recovered Recovered Recovered it rating the position of the corner: Bross Plus (cap) 13.79' PP Sp. W. Side 48.58' S.E. Cor. Barn 86.58' M.B.T. Pole Sp. N. Side In fon 44.5. Wif)