

# LAND CORNER RECORDATION CERTIFICATE

## FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF--	LOCATED IN--	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY <u>8</u> T. <u>4</u> N. <u>2</u> , R. <u>5</u> E.		<u>C-4, C-5</u>
2. PROPERTY CONTROLLING IN SECTION _____, T. _____, N. _____, S., R. _____, E. _____, W.		
3. MISCELLANEOUS PROPERTY IN SECTION _____, T. _____, N. _____, S., R. _____, E. _____, W.		
4. LOT NO. _____, RECORDED PLAT _____		
5. PRIVATE CLAIMS _____		

*LIVINGSTON*

REGISTER OF DEEDS STAMP AND FILING NUMBER

I, Donald L. Bissell, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on February, 1987, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on \_\_\_\_\_, 19\_\_\_\_, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

A. Description of original monument and accessories and/or subsequent restoration:

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

C-4 W 1/4 Corner Section 8 Found "T" iron set by Consumers Power Co. Replaced with 4" x 36" conc. mon. with alum cap	C-5 SW Corner Section 8 Found 1/2" iron rod
--	--

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

C-4 W 1/4 Corner Section 8 4" x 36" conc. mon. S34°E-29.25' - 18" Twin Oak S12°E-25.24' - 20" Triple B. Cherry S53°E-43.51' - 4" Hickory	C-5 SW Corner Section 8 1/2" iron rod N40°E-44.6' - 28" Shag Hickory N82°E-28.78' - 20" Shag Hickory S18°W-55.28' - 12" Poplar N86°W-23.17' - 4" x 6" fence corner post
--	--

SIGNED BY \_\_\_\_\_ DATE \_\_\_\_\_

SURVEYOR'S MICHIGAN REGISTRATION NO. \_\_\_\_\_

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY \_\_\_\_\_ DATE \_\_\_\_\_

APPROVED AND SIGNED BY Donald L. Bissell  
CHIEF OF SURVEY PARTY  
MICHIGAN REGISTERED LAND SURVEYOR

