

LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF--	LOCATED IN--	CORNER CODE NUMBER	
1. PUBLIC LAND SURVEY <u>8</u>	T. <u>4</u> N. <u>5</u> E. <u>4</u>	<u>E-3, E-4</u>	<i>LIVINGSTON</i>
2. PROPERTY CONTROLLING IN SECTION _____	T. _____ N. _____ S. _____ R. _____ E. _____ W. _____	_____	
3. MISCELLANEOUS PROPERTY IN SECTION _____	T. _____ N. _____ S. _____ R. _____ E. _____ W. _____	_____	
4. LOT NO. _____, RECORDED PLAT _____		_____	
5. PRIVATE CLAIMS _____		_____	

REGISTER OF DEEDS STAMP AND FILING NUMBER

I, Donald L. Bissell, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on February, 1987, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on _____, 19____, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

A. Description of original monument and accessories and/or subsequent restoration:

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

E-3 NE Corner Section 8
Found 1/2" iron rod

E-4 E 1/4 Corner Section 8
Found 1/2" iron rod at intersection
of old fences

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

E-3 NE Corner Section 8
Found 1/2" iron rod
N20°E-67.61' - 14" Oak
N50°E-65.02' - Thornapple clump
N64°E-83.19' - 16" Oak
N01°E-28.89' - Fence Corner

E-4 E 1/4 Corner Section 8
Set 4" x 36" conc. mon. with alum. cap.
S81°E-23.04' - 8" Elm
S71°E- 3.31' - 6" Elm
S45°E-24.35' - 10" Elm
S31°W-35.00' - 12" Elm

SIGNED BY _____ DATE _____

SURVEYOR'S MICHIGAN REGISTRATION NO. _____ (SEAL)

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY _____ DATE _____

APPROVED AND SIGNED BY Donald L. Bissell DATE 12-28-87
CHIEF OF SURVEY PARTY
MICHIGAN REGISTERED LAND SURVEYOR

