

LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF--	LOCATED IN--	CORNER CODE NUMBER	
1. PUBLIC LAND SURVEY <u>8</u> T. <u>4</u> N. <u>5</u> E.	<u>4</u> N. <u>5</u> E.	D-4, D-3	LIVINGSTON
2. PROPERTY CONTROLLING IN SECTION _____, T. _____, S., R. _____ E. W.	N. S., R. _____ E. W.	_____	
3. MISCELLANEOUS PROPERTY IN SECTION _____, T. _____, S., R. _____ E. W.	N. S., R. _____ E. W.	_____	
4. LOT NO. _____, RECORDED PLAT _____			
5. PRIVATE CLAIMS _____			

I, Donald L. Bissell, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on February, 1987, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on _____, 19____, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

A. Description of original monument and accessories and/or subsequent restoration:

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

<p>D-4 Center Section 8 Set 4" x 36" conc. mon. with alum. cap at inter. of N-S and E-W 1/4 lines.</p>	<p>D-3 N 1/4 Corner Section 8 Found "T" iron in fence corner set by Consumers Power Co. Replaced with 4" x 36" conc.mon. with alum. cap</p>
--	---

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

<p>D-4 Center Section 8 4" x 36" conc. mon. N11°E-57.75' - 5" Elm N72°E-27.70' - 6" Elm S22°W-40.00' - 8" W. Ash N16°W-21.18' - 4" Poplar</p>	<p>D-3 N 1/4 Corner Section 8 4" x 36" conc. mon. N71°W-27.20' - 18" W. Oak N50°W-36.65' - 18" Basswood N25°W-31.06' - 18" W. Oak N14°E-47.33' - 8" W. Oak (Old Witn)</p>
---	---

SIGNED BY _____ DATE _____

SURVEYOR'S MICHIGAN REGISTRATION NO. _____

(SEAL)

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY _____ DATE _____

APPROVED AND SIGNED BY Donald L. Bissell
CHIEF OF SURVEY PARTY
MICHIGAN REGISTERED LAND SURVEYOR

DATE 12-22-87

