

**SURVEY &  
REMONUMENTATION**

MAR 13 1998

**SECTION**

1997 Mackinac County Remonumentation Corner  
**LAND CORNER RECORDATION CERTIFICATE**  
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

<u>Mackinac</u> (County)	Located In:	Corner Code #
1. Public Land Survey	T43N R 1W	G-2
	T ___ R ___	_____
	T ___ R ___	_____
	T ___ R ___	_____
2. Property Controlling in Section	S ___ T ___ R ___	_____
	S ___ T ___ R ___	_____
3. Miscellaneous Property in Sec.	S ___ T ___ R ___	_____
	S ___ T ___ R ___	_____

RECEIVED & FILED  
DIANE HERRINGTON  
MACKINAC COUNTY REGISTER OF DEEDS  
DEC 31 1997  
AM  
REGISTER OF DEEDS STAMP & FILE NUMBER

4. Lot No. \_\_\_\_\_, Recorded Plat \_\_\_\_\_  
5. Private Claims \_\_\_\_\_

I, David B. Guthrie in a field survey on Dec. 17, 1997 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A	B	C	D	E	F	G	H	I	J	K	L	M
1												
2	6	5	4	3	2	1						
3												
4	7	8	9	10	11	12						
5												
6	18	17	16	15	14	13						
7												
8	19	20	21	22	23	24						
9												
10	30	29	28	27	26	25						
11												
12	31	32	33	34	35	36						
13												

A. Description of original monument and accessories and/or subsequent restoration:  
1840: G.L.O. Survey by J.H. Mullett - Set Post and Referenced.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:  
1997: Remonumentation Survey by R.S. Scott Associates, Inc.

SET 1/2" IRON ROD AT THE INTERSECTION OF THE NORTH-SOUTH ROAD AND OLD FENCE LINES EAST AND WEST.

ACCEPTED BY THE MACKINAC COUNTY SURVEY PEER GROUP AS THE OFFICIAL CORNER UNDER P.A. 345 OF 1990 AT A MEETING HELD ON 12-19-97

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:  
1997: Placed a 3" Mackinac County Cap stamped to identify the corner on a 1/2" Iron Rod.  
Referenced -

- N60W-1/2" IRON ROD-42.72 FEET
- S63W-1/2" IRON ROD-43.82 FEET
- S50E-1/2" IRON ROD-37.02 FEET
- EAST-1/2" IRON ROD-28.27 FEET



Signed by David B. Guthrie  
Surveyor's Michigan License No. 22435

Date: 12-22-97