

LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A. 1970
Mackinac Co.

FOR CORNERS OF--	LOCATED IN--	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY _____ T. <u>43</u> N. S., R. <u>6</u> E. W.		<u>M-13</u>
2. PROPERTY CONTROLLING IN SECTION _____, T. _____ N. S., R. _____ E. W.		
3. MISCELLANEOUS PROPERTY IN SECTION _____, T. _____ N. S., R. _____ E. W.		
4. LOT NO. _____, RECORDED PLAT _____		
5. PRIVATE CLAIMS _____		

REGISTER OF DEEDS STAMP AND FILING NUMBER

I, Billy D. Buckler, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on 6-13, 1977, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on _____, 19____, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

A. Description of original monument and accessories and/or subsequent restoration:

M-13 S.E. Corner Sec. 36, Twp. Cor. 42-43N R5-6W set by Wm. A. Burt, D.S. in 1840.
Bearings were:
Hemlock 12, N40°E, 12 lks. and hemlock 30, S36°W, 39 lks.


B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

M-13 Found 1½" iron pipe, set by Marcus Schaaf, R.L.S., 1937.
Notes by Schaaf on Page 60, Field notebook, 42-6W.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

M-13 Re-witnessed Twp. Cor. as found by Schaaf. New bearings:
10" R. Pine, S83°W, 23.0' -
12" Red Pine, S78°E, 7.7' and 12" Red Pine, N30°E, 10.0'

SIGNED BY Billy D. Buckler DATE 3-19-80
SURVEYOR'S MICHIGAN REGISTRATION NO. _____



FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY _____ DATE _____
CHIEF OF SURVEY PARTY

APPROVED AND SIGNED BY _____ DATE _____
MICHIGAN REGISTERED LAND SURVEYOR (SEAL)

SURVEYOR'S MICHIGAN REGISTRATION NO. _____