

LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

Mackinac Co.

3 Corners.

FOR CORNERS OF--:	LOCATED IN--:	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY _____ T. _____	N. _____ E. _____ S., R. _____ W.	_____
2. PROPERTY CONTROLL- ING IN SECTION <u>3</u> , T. <u>43</u>	N. _____ E. _____ S. , R. <u>7</u> W.	<u>8, 11, 11A</u>
3. MISCELLANEOUS PROPERTY IN SECTION _____ , T. _____	N. _____ E. _____ S., R. _____ W.	_____
4. LOT NO. _____ , RECORDED PLAT _____		
5. PRIVATE CLAIMS _____		

REGISTER OF DEEDS STAMP AND
FILING NUMBER

I, David B. Babbitt, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on 10-25 & 10-24, 1983, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on _____, 19____, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

A. Description of original monument and accessories and/or subsequent restoration:

- 8 West 1/16 corner of section 3. Not prev. established.
- 11 Southwest 1/16 corner of section 3. Billy D. Luckler, R.L.S. in 1981. 8" J. Pine, S16°E, 55.3' & 12" J. Pine, N59°E, 33.5'.
- 11A 1/64 corner north of the southwest 1/16 corner of section 3. Billy D. Luckler, R.L.S. in 1981. 16" R. Pine, N30°E, 17.2' & 8" R. Pine, S15°E, 30.0'.

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

- 8 Corner placed midway between the west 1/4 corner and the center corner of section 3.
- 11 Corner adjusted to new location of east 1/4 corner of sec. 4. Corner placed at intersection of lines connecting opposite 1/16 corners.
- 11A Corner adjusted to new location of east 1/4 corner of sec. 4. Corner set midway bet. southwest 1/16 corner and the west 1/16 corner of section 3.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

- 8 1" pipe W/Plastic RLS cap buried. Bearings: 8" J. Pine, N41°W, 37.7' & 12" J. Pine, N23°W, 38.6' & 12" R. Pine, S69°E, 49.4' & 10" R. Pine, S31°E, 33.5'.
- 11 DNR Monument. Bearings: 12" J. Pine, N27°E, 56.1' & 14" J. Pine, N8°E, 28.7' & 12" J. Pine, S55°E, 44.3' & 8" J. Pine, S12°E, 67.1'.
- 11A DNR Monument. Bearings: 14" J. Pine, N36°E, 1.4' & 22" R. Pine, S68°E, 7.6' & 12" R. Pine, S11°E, 48.2' & 6" J. Pine, S80°W, 31.4'.

SIGNED BY

David B. Babbitt
David E. Babbitt

DATE 11-21-83

SURVEYOR'S MICHIGAN REGISTRATION NO.

21558

(SEAL)

FOR STATE AND UNITED STATES AGENCIES: