

**FILING REQUIREMENT OF ACT 74, MICH. P.A. 1970**

Mackinac Co.

2 Corners.

FOR CORNERS OF--	LOCATED IN--	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY _____ T. _____ N. S., R. _____ E. W.		
2. PROPERTY CONTROLLING IN SECTION <u>9</u> , T. <u>43</u> , N. S., R. <u>7</u> E. W.		<u>9, 2</u>
3. MISCELLANEOUS PROPERTY IN SECTION _____, T. _____ N. S., R. _____ E. W.		
4. LOT NO. _____, RECORDED PLAT _____		
5. PRIVATE CLAIMS _____		

REGISTER OF DEEDS STAMP AND  
FILING NUMBER

I, David B. Babbitt, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on 6-3 & 6-23, 1983, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on \_\_\_\_\_, 19\_\_\_\_, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

A. Description of original monument and accessories and/or subsequent restoration:

- 9 East 1/16 corner of section 9. Not prev. set.
- 2 East 1/16 corner on north side of section 9. Not prev. set.

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

- 9 Corner set M.P.O.L. between center corner and east 1/4 corner of section 9.
- 2 Corner set M.P.O.L. between NE corner and computed N1/4 corner of section 9.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

1" pipe w/plastic RLS cap buried in road at both corners. Bearings:

- |   |               |        |       |   |               |        |        |
|---|---------------|--------|-------|---|---------------|--------|--------|
| 9 | 12" H. Maple, | S28°E, | 36.0' | 2 | 12" H. Maple, | S37°E, | 52.9'  |
|   | 12" H. Maple, | S15°W, | 32.6' |   | 7" H. Maple,  | S1°W,  | 39.0'  |
|   | 10" Beech,    | N37°W, | 37.8' |   | 5" H. Maple,  | S41°W, | 61.95' |
|   | 8" R. Maple,  | N37°E, | 31.1' |   | 6" R. Maple,  | N78°W, | 54.3'  |

SIGNED BY

*David B. Babbitt*

DATE 8-18-83

David B. Babbitt  
SURVEYOR'S MICHIGAN REGISTRATION NO. 21558

(SEAL)

FOR STATE AND UNITED STATES AGENCIES: