

FILING REQUIREMENT OF ACT 74, MICH. P.A. 1970
Mackinac Co. 2 Corners.

FOR CORNERS OF--	LOCATED IN--	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY _____	T. <u>43</u> N. <u>11</u> E. <u>W.</u>	D-7
2. PROPERTY CONTROLLING IN SECTION <u>17</u>	T. <u>43</u> N. <u>11</u> E. <u>W.</u>	16
3. MISCELLANEOUS PROPERTY IN SECTION _____	T. _____ N. _____ E. _____	
4. LOT NO. _____, RECORDED PLAT _____		
5. PRIVATE CLAIMS _____		

REGISTER OF DEEDS STAMP AND
FILING NUMBER

I, David E. Eabbitt, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on 6-18, 1982, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on _____, 19____, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

A. Description of original monument and accessories and/or subsequent restoration:

- 7 1/4 cor. on south side of sec. 17. Wood Post, Cedar 4", S10°E, 40 lks. & Spruce 6", N5°W, 6 lks.
- 6 East 1/16 cor. on south side of sec. 17. Not previously established.

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

- 7 Corner set M.P.O.L. between SW section corner and SE section corner of section 17.
- 6 Corner set M.P.O.L. between South 1/4 corner and SE section corner of section 17.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

- | | |
|-----------------------------------|-------------------------------|
| -7 D.N.R. Monument. New Bearings: | 16 D.N.R. Monument. Bearings: |
| 5" Tamarack, N62°E, 9.6' | 10" Twin Spruce, N02°E, 59.4' |
| 6" Tamarack, S19°W, 1.5' | 10" R. Maple, N47°W, 41.7' |
| 7" Tamarack, S50°E, 24.1' | 14" Spruce, N41°E, 47.3' |
| 4" Cedar, N55°W, 13.5' | 12" Aspen, S53°E, 32.3' |

SIGNED BY David E. Eabbitt
David E. Eabbitt

DATE 8-3-82

SURVEYOR'S MICHIGAN REGISTRATION NO. 21558

(SEAL)

FOR STATE AND UNITED STATES AGENCIES: