LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

MACKINAC CO. 3 CORNERS

FOR CORNERS OF—:	LOCATED IN—:	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY	T. 43 N. S., R. 12 E. W.	E-8, E-9
2. PROPERTY CONTROLLING IN SECTION 21	,T. 43 N. S., R. 12 E. W.	1
3. MISCELLANEOUS PROPERTY IN SECTION	,T. N. S., R. E. W.	

4. LOT NO. _____ , RECORDED PLAT _____

5. PRIVATE CLAIMS _____

REGISTER OF DEEDS STAMP AND FILING NUMBER

I, Gerald L. Wiggins, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on 2-27 & 4-29, 1985, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on _____, 19____, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

A. Description of original monument and accessories and/or subsequent restoration:

E-8 West 1/4 Corner of Section 21. OBT'S: Tam 8, N40°E, 7 lks. & 6" Tam., S71°W, 20 lks.

E-9 Southwest Corner of Section 21. OBT'S: Cedar 14, N20°E, 13 lks. & Tam. 9, S46°W, 11 lks.

1 West 1/16 Corner on North side of Section 21. Not prev. set.

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

E-8 Corner set M.P.O.L. between NW Section Corner and SW Section Corner of Section 21.

E-9 Corner set by Double Proportionate Measure between Sec. Cor. 1 mile West, 1/4 Cor. 1/2 mile East, Sec. Cor. 1 mile North, and Meander Corner 1097.83' South. Measurements compare with US #2 R.O.W. Plans.

1 Corner set M.P.O.L. between NW Sec. Cor. and North 1/4 Corner of Section 21.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner DNR MONUMENTS except E-9

E-8
6" Cedar, N75°W, 17.3'
6" Cedar, S34°W, 12.1'
8" Cedar, S50°E, 8.0'
7" Cedar, N80°E, 23.9'

1
12" Cedar, S23°E, 23.1'
8" Cedar, S53°E, 14.1'
10" Cedar, N24°W, 9.7'
9" Cedar, S81°W, 17.3'

E-9
1" Pipe W/Plastic cap
5" Tam., N15°E, 49.6'
8" Tam., N72°E, 119.8'
12" Tam., S45°E, 184.8'
14" Tam., S35°E, 175.4'
Center Line US#2, South 14.55'

SIGNED BY Gerald L. Wiggins DATE 9-11-86

Gerald L. Wiggins

SURVEYOR'S MICHIGAN REGISTRATION NO. 23521

STATE OF MICHIGAN GERALD L. WIGGINS LAND SURVEYOR (SEAL) No. 23521 REGISTERED