

FOR CORNERS OF--	LOCATED IN--	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY_____ T. _____ N. S., R. _____ E. W.		
2. PROPERTY CONTROLLING IN SECTION <u>17</u> T. <u>44</u> N. S., R. <u>11</u> E. W.		<u>8, 3, 4</u>
3. MISCELLANEOUS PROPERTY IN SECTION _____ T. _____ N. S., R. _____ E. W.		
4. LOT NO. _____, RECORDED PLAT _____		
5. PRIVATE CLAIMS _____		

REGISTER OF DEEDS STAMP AND FILING NUMBER

I, David E. Babbitt, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on 1-7, 1983, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on \_\_\_\_\_, 19\_\_\_\_, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

## A. Description of original monument and accessories and/or subsequent restoration:

- 8 West 1/16 Cor. <sup>E-W line</sup> Sec. 17. Not prev. est.
- 3 North 1/16 Cor. on West side of Sec. 17. Not prev. est.
- 4 Northwest 1/16 Cor. Sec. 17. Not prev. est. (CENTER OF NW 1/4)

## B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

- 8 Set M.P.O.L. between center corner and west 1/4 corner. Corner lies 65' South of old E-W Road.
- 3 Set M.P.O.L. between N.W. section corner and West 1/4 corner of section 17. Corner lies 65' East of N-S power line.
- 4 Set at center of NW 1/4 by closed traverse.

## C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

D.N.R. Monuments placed at all three corners.

- |                             |                              |                          |
|-----------------------------|------------------------------|--------------------------|
| 8 10" Hemlock, N62°W, 25.8' | 3 10" W. Birch, S13°E, 20.3' | 4 8" Cedar, S50°W, 34.0' |
| 6" Hemlock, N40°W, 34.1'    | 10" Spruce, S74°E, 22.3'     | 6" Cedar, S3°W, 13.2'    |
| 9" Aspen, S10°W, 20.9'      | 12" Spruce, S68°W, 14.7'     | 6" Cedar, N76°E, 36.2'   |
| 8" Cedar, S84°W, 21.8'      | 7" Spruce, N30°W, 9.9'       | 8" Cedar, N55°E, 27.45'  |

SIGNED BY

*David E. Babbitt*

David E. Babbitt

DATE 1-26-83SURVEYOR'S MICHIGAN REGISTRATION NO. 21558

(SEAL)

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY \_\_\_\_\_

DATE \_\_\_\_\_