

4	4	
2	3	Plot corner in cent Ryoo Rd.
2	3.6	iron rod. most south. of 3 iron rods at intsect of Hamlin Rd.
2	4	set brass S.C. 2/6, 6" below surface, brick, broken coal, glass (Reported to Co Rd Comm) W. edge asph. pave. N. 20° W. 57.93' horiz. spike in NE side 5" wild cherry. S 85° E. 32.67' to horiz spike in 20" ash. S 27° 30' E 66.20' horiz. spike in NE side 16" ash set brass S.C. head of 30" iron increased in center
4	4	PK spike in N. end RR. Xing planks at & bet. rails; N 69° E 39.56' to 4" R.R. semaphore Pipe; N 82° E 99.92' W. end N. conc bridgeabut; S 54° W 54.80' E R.R. semaphore pipe; N 80° W 74.94 to & transformer pole. (1960) Reported to Co Rd Comm iron rod at S. end Curtis-Wright tracks. between N edge pave + cyclone fence
4.3	4	iron rod intsect. Shelby + 22 mi. Rds.
3	4	Cor between Sec 30 & 29 4" brass S.C. marker on 1" iron pipe; N 79° E 25.35' to horiz spike. in S. side of 6" maple - S 87° E 54.80' to horiz spike S side 30' oak; N 33° 30' E, 30.15' to horiz spike in E side 12" elm; S 60° W 47.17' to horiz spike in N side of 24" oak; S 87° 46' 52" W 178.33 to next 1 1/2" iron pipe on sec line W. and in E of old stream channels. (1960) Reported Co Rd Comm.