

LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A. 1970

FOR CORNERS OF--:	LOCATED IN--:	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY <u>30</u>	T. <u>4</u> N. <u>X</u> , R. <u>14</u> E. <u>X</u>	<u>A-11</u>
2. PROPERTY CONTROLLING IN SECTION <u>30</u>	T. <u>4</u> N. <u>X</u> , R. <u>14</u> E. <u>X</u>	<u>A-11</u>
3. MISCELLANEOUS PROPERTY IN SECTION _____	T. _____ N. _____, R. _____ E. _____	_____
4. LOT NO. _____, RECORDED PLAT _____		
5. PRIVATE CLAIMS _____		

REGISTER OF DEEDS STAMP AND FILING NUMBER

(2)

I, D. Scott do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above (identified with circles on index code diagram - over) were, in a field survey on JUNE 30 1923, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on JUNE 30 1923, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

A. Description of original monument and accessories and/or subsequent restoration:

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

*Pointed Stone with 1/2" Iron Rod by it.
Stone recovered with directions given by P.F. SONSTADT a 67 year old
property owner. Who stated that the pointed stone had been there as
long as his father could remember. His father had owned the property in 1930*

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Pointed Stone with 1/2" Iron Rod by it

N. 40° E.	72.0'	S.E. Cor Bldg.
N. 20° W.	46.3'	Well with Pump
N. 12° W.	62.4	S.W. Cor. Bldg.
S. 18° E.	61.0'	6" Hickory
South	52.8'	1/2" Iron Pipe

SIGNED BY _____ DATE _____

SURVEYOR'S MICHIGAN REGISTRATION NO. 12029 (SEAL)

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY _____ DATE _____
CHIEF OF SURVEY PARTY

APPROVED AND SIGNED BY _____ DATE _____
MICHIGAN REGISTERED LAND SURVEYOR (SEAL)

SURVEYOR'S MICHIGAN REGISTRATION NO. _____