

# LAND CORNER RECORDATION CERTIFICATE

## FILING REQUIREMENT OF ACT 74, MICH. P.A. 1970

FOR CORNERS OF--	LOCATED IN--	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY _____	T. <u>21</u> N. <u>8.</u> , R. <u>16</u> E. <u>W.</u>	<u>B-3; C-3</u>
2. PROPERTY CONTROLLING IN SECTION <u>6</u>	T. <u>21</u> N. <u>8.</u> , R. <u>16</u> E. <u>W.</u>	<u>12</u>
3. MISCELLANEOUS PROPERTY IN SECTION _____	T. _____ N. _____, R. _____ E. _____	_____
4. LOT NO. _____, RECORDED PLAT _____		_____
5. PRIVATE CLAIMS _____		_____

REGISTER OF DEEDS STAMP AND FILING NUMBER

I, Carl F. Roser do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above (identified with circled index code diagram - over) were, in a field survey on November 15 1973, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on 19, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Professional Surveyors or, by a Decree of a Court of law:

**A. Description of original monument and accessories and/or subsequent restoration:**

**B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:**

- B-3 Recovered old corner of record. More recently used by R.L.S. Tony Slawinski.
- C-3 Recovered old corner of record. More recently used by R.L.S., Tony Slawinski.
- 12 Recovered NE cor. of Govt. lot 10, per survey by RLS Tony Slawinski, Aug. 1966.

**C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:**

B-3	C-3	12
Fd 1 1/2" iron shaft in S. edge of E-W Rd.	Fd 1" iron rod	Fd 1/2" pipe & 1 1/2" x 6' - alum. tube
USGS conc. marker N46W 63.59	9" oak N14E 41.61'	30" Willow S25E 210.20'
4" pipe Due South 32.8	12" oak S27E 51.90'	28" Willow S62E 181.75'
16" power pole N68W 22.68	10" oak S41W 55.18'	
	Ctr. E-W B. Top Co. Rd. 4.0'	

SIGNED BY \_\_\_\_\_ DATE March 13, 1974

SURVEYOR'S MICHIGAN REGISTRATION NO. 12028 (SEAL)

**FOR STATE AND UNITED STATES AGENCIES:**

SIGNED BY \_\_\_\_\_ DATE \_\_\_\_\_  
CHIEF OF SURVEY PARTY

APPROVED AND SIGNED BY \_\_\_\_\_ DATE \_\_\_\_\_  
MICHIGAN REGISTERED LAND SURVEYOR (SEAL)

SURVEYOR'S MICHIGAN REGISTRATION NO. \_\_\_\_\_

Form No. MLM738  
 CONSULT THE BUREAU OF LAND MANAGEMENT, WASH. D.C.

FORM APPROVED BY MICHIGAN STATE BOARD OF REGISTRATION, JAN. 28, 1971  
 DISTRIBUTED BY MICHIGAN SOCIETY OF REGISTERED LAND SURVEYORS