

LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF--	LOCATED IN--	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY _____	T. 21 ^{N.} R. 16 ^{W.}	K-10; L-9; M-10
2. PROPERTY CONTROLLING IN SECTION 25 _____	T. 21 ^{N.} R. 16 ^{W.}	8
3. MISCELLANEOUS PROPERTY IN SECTION _____	T. _____ ^{N.} _{S.} R. _____ ^{E.} _{W.}	_____
4. LOT NO. _____, RECORDED PLAT _____		
5. PRIVATE CLAIMS _____		

REGISTER OF DEEDS STAMP AND FILING NUMBER

I, Carl F. Roser do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above (identified with circles on index code diagram - over) were, in a field survey on September 17, 1974, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on _____ 19____, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

A. Description of original monument and accessories and/or subsequent restoration:

C. (continued)

8


Set 1"x36" pipe & cedar post		
10" W. Oak	N05°E	22.9
2" W. Pine	N82°E	28.7
7" Oak	S55°E	8.5

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

- K-10 Reestablished corner per standard B.L.M. instructions.
- L-9 Reestablished corner per standard B.L.M. instructions.
- M-10 Accepted corner as recovered, witnessed and recorded by RLS Ken Ross.
- 8 Established corner per standard B.L.M. instructions.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

K-10	L-9	M-10
Set DNR mon. & cedar post	Set DNR mon. & cedar post	Fd. 2" pipe & added DNR mon. & cedar post
6" W. Pine S63°E 13.5	13" W. Pine N70°E 30.5	12" W. Oak N40°W 55.17
5" W. Pine S35°W 30.4	12" W. Pine S45°E 17.4	12" R. Pine N75°W 109.05
N-S power line Due E 112'	12" W. Pine Due S 11.3	8" R. Oak S70°E 27.57



SIGNED BY _____ DATE _____

SURVEYOR'S MICHIGAN REGISTRATION NO. 12028

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY _____ DATE _____

APPROVED AND SIGNED BY _____ DATE _____

SURVEYOR'S MICHIGAN REGISTRATION NO. _____

STRONACH TOWNSHIP
MANISTEE COUNTY