SURVEY & REMONUMENTATION

APR 0 7 1998

LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. P.A. 1970

or corners in SECTION (County)	Located in:	Corner Code #	1	REGISTER'S OFFICE MANISTEE COUNTY #91-383 AT 11:00 A-M- OCT 1 4 1997			
Dublic Land Currou	T 21W D 14W	M-13					
. Public Land Survey	T 21N R 14W T R	M-12		Anny	a. Peper	<u>J</u>	
•	Ţ		•	REGISTE	R OF DEED	S	
■. Property Controlling S	TR T R						
in Section S	T R R						
3. Miscellaneous S Property in Sec. S	T R		Register	of Deeds S	temp & File	Number	
Property in Sec. S	'						
Lot No, Records Private Claims	d Plat		, <u>A</u>	BCDI	FGH	I J K L	. M
D. Pitvate Claims			2	6 5	4 3	2	•
			3				4-1
E, Kenneth L. Ross mio hereby certify that under requirem	, in a field surve	yon <u>July 31</u> 19 97	4 ·	7 8	9 10	111	12
En lines 1 and 2 above were in con-	formance with regulations an	d rules therefore as required in t	the j			┟╌╁╌	$\overline{}$
ecurrent manual of survey instructions Management or by a decree of a Cou	of the United States Departs	nent of the Interior, Bureau of Lar	nd 6	18 17	16 15	14	13
shove were in conformance with the	rules of the Michigan Board of	f Land Surveyors or by a Decree of	fa	19 20	21 22	23	24
■Court of Law; established, re-established, re-established	tablished, monumented, re-	monumented, recovered, tound	28 9 -				
none Alakaan Alaa Aman			20	30 29	28 27	26	25
NOTE: Not more than 4 corn on this certificate.	ers, an in the same town	and range, may be recorde	" 11			╂╌┼╌╂╌	+
			12	31 32	33 34	35	36
A. Description of original mor M-13 Section Corner for	Nument and accessories at <u>Bections 36, T21N-R14N</u>	nd/or subsequent restoration: r_and_section_31,_T21N-R13	13 L		<u> </u>	lil	
	# 15 lks.(9.9) E 35 lks.(23.10) #5489 wood stake from measur two red pine trees by	tunknown imp) brass cap corner M = 13 according to the co	47 R. P libe 1992, Re Found 2" used in witnesse ratification vian ado	eine 8" er 4 - pg. owe Engineer Tron Pipe cadastral es were add	N 10° E 47 34 & 35 ring Inc. W/ 3 1/4" Survey, no ed. nistee County of to P.A. 34	Brass ca new Peer Grou 15 of 199	r) PP Up IO
B. Description of corner evidence M-13 Section Corner for Section Corn	ence found and/or methodections 36, T21N-R14W	dpp://districtions.	olishing corner		7 >		·
On July 31, 1997, I Ken Ro George Blass, as surveyed feet above ground surface.	oss and Kevin Pritchar , Liber 1 Page 34, 35	i (survey tech.) found 2". . Monument sets 8 feet No.	steel pipe to orth of road	with 3 1/4" erosion on	brass cap, bank of hi	set by 11, 1.8	
Condition of record witner \$5 Gone \$6 Gone \$7		ine Stump #2 Gone #3	Gone #4	Found in g	good conditi	on	
M-13 Section Corner for S	ections 36, T21N-R14W		•			hr tha	
I accepted George Blass corner as a substantial corner.	marker for the corner	ed with concrete, with 3 and is accepted as a per	petuation of	the positi	on or the	MCHIG	Park.
EBT #4 White Oak 8" N 2 White Oak 7" N 0		spike in NW side of tree) spike in SE side of tree)		Š	EG KENNETH	L. ROSS	12 =
White Oak 13" 8 7	0° W 48.58' (set 60d s	mpike in SE side of tree)		121	2	ND	9,7
White Oak 10" N 6	Ų K 24.¥2'(\$85 60₫)	spike in SE side of tree)		7418:	. •	VEYOR	
	_			ži.	17	lo. 6 3 / a	3 8
	$\mathscr{L}(\mathcal{N})$	_	/	' - مس	130	400	C. III
Signed by Lane	1 Kon	Date Au	945/	29, 1	99,3950	300	17.
Surveyor's Michigan Liganca No.	17634	•	FORM APPROV	AND INV MATERIAN STA	TEBOARD OF LAND S	urveyora Ian	28, 1971