## SURVEY & REMONUMENTATION

DEC 1) 9 1999

## LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970

For corners in SECT	IOM		1
<u>Manistee</u>	Located In:	Comer Code #	REGISTER'S OFFICE
(County)			MANISTEE COUNTY
	T CON DIAGNAL	M-11 SE cor. Sec. 25	99 327 1 1100
Public Land Survey	T <u>22N</u> R <u>15W</u> T <u>22N</u> R <u>14W</u>	A-11 7	99-327at 41:05pm SEP 29 1999
	TR	CH-III	
·	TR		Daborah Six
2. Property Controlling	S T R		REGISTER OF DEEDS
in Section	S TR S TR	-	TEGOTE TELEGO
3 Miscellaneous	STR		
Property in Sec	_s TR		Register of Deeds Stamp & File Number
			ABCDEFGHIJKLM
	1 101-4	•	
4. Lot No, Record			2 -6-+-5432-7-1-1
5. Private Claims			3
		•	4 - 7 - 8 9 10 11 12-
			5
1, Bruce J. Jenema	, in a field survey	on <u>April 29</u> , 19 <u>99</u> do	6 18 17 16 15 14 13
hereby state that under requirem	ents of P.A. 74, Michigan P.A. of		
lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land			
Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4			8 -19 -20 -21 -22 -23 -24
and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, reestablished, monumented, recovered, found as expressed			9
below:			10 30 29 28 27 26 25
			11
NOTE: Not more than 2 corners, all in the same town and range, may be recorded			12 31 32 33 34 34 35 36
on this certificate.			13
A. Description of original subsequent restoration		s and/or	THE OF MICHIGAN
M-11 T22N, R15W (SE co	enor Soction 25) Comme	nn to Δ-11 T22N R14W	ART SUCCE IN
WI-11 122N, R15W (SE CO	Milei Section 25/ Commit	// (O //-11 122H, 13444	\@\ DI(OO= - \
1837 J. Brink, D.S. GLC	)	1909 Fargo Enginee	ering JENEMA
			age 131 & Bk 1 pg 118
1.) 16" W. Pine S63°W 40 links (26.40') No U.S. evidence 2.) 10" Hemlock N63°W 12 links (7.92') 3.) 16" W. Oak S8			4°E 0.62 ch. (40.92')
2.) 10" Hemiock No3"V	V 12 links (7.92)	4.) 6" R. Oak S62 3	3/4°W 0.41 ch (27.06')
1980 G.A. Fauser (C.P.	Co)	,	aring lage 131 & Bk 1 pg 118 SURVEYOR NO. 25850 314°W 0.41 ch (27.06')
Rec. Liber 1, page 809 of surveys		1986 A.M. Slawinsi	(i )
Found 1" pipe Set by Fargo 5.) 13" R. Pine S70°E 33.30'		Unrecorded Found Iron pipe	
6.) 23" W. Oak S80°E	48.65'	No reference given	1000
7.) 25" W. Pine S05°E		•	
8.) 12" R. Pine S10°W	27.09'		30 1 7
	now extinct Witnesses 3 & 6 r		The same of the sa
B. Description of corner	evidence found and/or me	thod applied in restoring or ree	stablishing comer:
	nd a 1 1/4" iron pipe hooked a 6.), 7.), & 8.)	t the base and lime deposited by	Fargo Engineering
No conflicting evidence	of other corners existing.		
C. Description of monume position of the corner:	ent for corner and accesso	ries established to perpetuate I	cocating the
On July 14,1999, I place accepted as the best av	ed a standard Manistee Coun ailable evidence of the position	ty Monument in the exact position on of the original corner and witne	ssed by: 기를 일
7.) 26" W. Pine S05°E	29 00' Nail E. side	t 60-D spike in same location 9.) 14" W. Oak S7	0°E 48.65' Found Nail & washer N. side 5°W 21.41' Set 60-D N. side the West and 30'North from the base of a
Signed by Bruce f.	1	•	4.4.60
Signed by Bruce f.	yenema _	Date	9-16-99
Surveyor's Michigan License	· ·		
		FORM APPROVED BY	NICHIGAN STATE BOARD OF PROFESSIONAL SURVEYORS