

MANISTEE COUNTY
LAND CORNER RECORDATION CERTIFICATE
 FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF--	LOCATED IN--	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY _____	T. <u>23</u> N. S., R. <u>14</u> E. W.	G-2 H-3 G-3 I-3
2. PROPERTY CONTROLLING IN SECTION <u>3</u>	T. <u>23</u> N. S., R. <u>14</u> E. W.	Code 10
3. MISCELLANEOUS PROPERTY IN SECTION _____	T. _____ N. S., R. _____ E. W.	
4. LOT NO. _____, RECORDED PLAT _____		
5. PRIVATE CLAIMS _____		

REGISTER OF DEEDS STAMP AND
FILING NUMBER

I, Carl F. Roser do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above (identified with circles on index code diagram - over) were, in a field survey on 10-26-72 19___, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on _____ 19___, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

~~XX~~ C. continued

<p style="text-align: center;">I-3</p> <p>Fd. 1 1/4" Pipe 24" Oak N17E 79.40' P. Pole N24E 55.92' B. Cherry N76E 161.90' Fn. to N & S Due W 17.5' Ctr E-W Gr.Rd Due S 1'</p>	<p style="text-align: center;">Code 10</p> <p>Set 1"x36" Pipe & Old Cedar Fence Post with Location Tag in line with fence remains to W. 4" R. Pine N 20 W 68.62' 6" Pin Cherry N 89 W 28.92'</p>
--	---

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

G-2)
 G-3) Recovered corner per J.H. Millard (deceased Co. Surveyor) survey (1914-1915) of
 H-3) record: see old red "Surveyors Record" (large book), Pg. 194, at Manistee County
 I-3) Register of Deeds.

Code-10 Established corner by single proportion.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

<p style="text-align: center;">G-2</p> <p>Fd. 1 1/4" pipe buried 0.5' 5" R. Pine S40W 38.4' (cor. Pine Plant) 4" R. Pine N27W 48.2' (cor. Pine Plnat)</p>	<p style="text-align: center;">G-3</p> <p>Fd. 1 1/4" Ir. Pin-buried 0.4' P. Pole Transf. N72E 92.13' 37" Pole S43E 39.92' 7" R. Pine S42W 70.94' Approx. Int. Grave/Roads S-E-W. N72W 17'±</p>	<p style="text-align: center;">H-3</p> <p>Fd. 3/4" Sq. Hd. Bolt in line with Fn. remains S. Added DNR Monument P. Pole N69W 98.63' 6" W. Pine S46E 67.67' 14" Scotch Pine S3E 52.32' E-W Gr. Rd Due S 2'± Fen. Remains N Due E. 10'±</p>
--	--	--

SIGNED BY Carl F. Roser DATE 11-6-72

SURVEYOR'S MICHIGAN REGISTRATION NO. 12028

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY _____ DATE _____
CHIEF OF SURVEY PARTY

APPROVED AND SIGNED BY _____ DATE _____
MICHIGAN REGISTERED LAND SURVEYOR

