LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF–:	LOCATED IN–:	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY	T. 24 N. S., R. 14 E. W.	A-8 A-9 B-9
2. PROPERTY CONTROLLING IN SECTION 19	,T. 24 N. S., R. 14 E. W.	14
3. MISCELLANEOUS PROPERTY IN SECTION	,T. N. S., R. E. W.	

4. LOT NO. _____ , RECORDED PLAT _____

5. PRIVATE CLAIMS _____

REGISTER OF DEEDS STAMP AND FILING NUMBER

I, Carl F. Roser, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on October 11, 1978, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on _____, 19____, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

~~A. Description of original monument or subsequent~~

C. continued

14

Set 5/8"X40" re-rod w/RLS Cap
& Ced. Post w/Loc. Tag.

8" Maple	N50°E	11.75
2-6" Maples	S40°E	23.68
Ctr. N-S B.Top County Rd.		
	Due W	29.8'

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

A-8 Fd. Dept. Monument; previous Dept. Corner of record, 1961.

A-9 Fd. Dept. Mon. (1" pipe w/Alum. Cap broken off) as estab. in previous Dept. Survey (1961) by single proportion, N. one mile & S. one mile.

B-9 Re-estab. 1/4 Corner on line between Sec. Corners to E&W and at pro-rated distance to orig. G.L.O. survey. Also see Cor. Rec. for SW Cor. Sec. 20.

14 Established 1/8 Cor. equidistant & on line between Sec. Cor. to S. & 1/4 Cor. to N.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

A-8			A-9			B-9		
Fd. DNR Mon.; added Ced.Post			Fd. Dept. Mon. & added Ced.Post			Set D.N.R. Mon. & Ced.Post		
3" Maple	N25°W	23.8'	8" Maple	S54°E	12.9	8" Maple	N20°E	26.8
4" Maple	N35°E	29.8'	7" Maple	N36°W	34.0	10" Trp.Maple	N73°E	77.1
3" Maple	S55°W	40.0'	13" Maple	S58°W	24.2	16" Trp.Maple	N25°W	53.1
Ctr. N-S Trail			7" Maple	N65°E	15.8	E-W random	Due N.	2.6'
	Due W	20'±	Ctr. N-S trail					
				Due W.	14'±			

SIGNED BY Carl F. Roser 2-26-79 DATE _____

SURVEYOR'S MICHIGAN REGISTRATION NO. 12028

STATE OF MICHIGAN CARL F. ROSER LAND SURVEYOR No. 12028 REGISTERED LAND SURVEYOR (SEAL)

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY _____ DATE _____
CHIEF OF SURVEY PARTY

APPROVED AND SIGNED BY _____ DATE _____
MICHIGAN REGISTERED LAND SURVEYOR

(SEAL)
SPRINGDALE TOWNSHIP
MANISTEE COUNTY

SURVEYOR'S MICHIGAN REGISTRATION NO. _____

FORM APPROVED BY MICHIGAN STATE BOARD OF REGISTRATION, JAN. 28, 1971
REVISED MAY 14, 1975

MAY PLACE SKETCH ON BACK OR ATTACHED SHEET