LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF—:	LOCATED IN—:	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY _____	T. 24 N. S., R. 14 E. W.	D-9
2. PROPERTY CONTROLLING IN SECTION 20,	T. 24 N. S., R. 14 E. W.	3; 13; 14; 15
3. MISCELLANEOUS PROPERTY IN SECTION _____,	T. _____ N. S., R. _____ E. W.	
4. LOT NO. _____, RECORDED PLAT _____		
5. PRIVATE CLAIMS _____		REGISTER OF DEEDS STAMP AND FILING NUMBER

I, Carl F. Roser, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on October 9, 19 78, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on _____, 19____, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

~~A. Description of original monument and accessories and/or subsequent restoration~~

C. continued

14			15		
Fd. 1"X30" pipe & Set ced.post w/Loc. Tag.			Drove 5/8"X40" re-rod w/RLS Cap & Ced.Post w/Loc. Tag.		
7" Tw.Maple	N08°W	52.1	8" Cedar	N83°W	76.3'
4" Maple (clump)	N60°E	79.2	5" Maple	N10°W	3.8'
6" Cherry (Twin)	S18°E	61.3	Ctr. of E-W		
S.Bank Bear Cr.	Due N	170'±	dirt Co. Rd.	Due S.	324'(±2')

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

D-9 —— Re-established 1/4 Cor. equidistant & on line between Sec. Corner's to E & W. Also see item B, SW Cor. Sec. 20, Cor. Code C-9.

3 —— Established 1/8 Corner equidistant & on line between fd. NE & E 1/4 Cor's. of Sec. 19. Old fence to W, starts W. from W. side of road, is 7'± to South.

14 —— Fd. & accepted 1" pipe by RLS, Tony Slawinski; Cert.Sur., Liber 1, Pg. 50, June 1972.

13 —— Established Ctr. of SE 1/4 of Sec. 20 per Std. B.L.M. instructions.

15 —— Established 1/8 Corner equidistant & on line between Sec. Cor. to W. & 1/4 Cor. to E.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

D-9			3			13		
Set DNR Mon. & Ced.Post.			Drove 5/8"X40" Re-rod w/RLS Cap & Ced.Post w/Loc. Tag.			Drove 5/8"X40" re-rod & Ced.Post w/Loc. Tag.		
7" Cedar	N69°E	22.9	7" Cedar	S75°W	9.9	9" Sugar Maple	S20°W	26.3
8" Cedar	N25°E	39.8	13" Ash	S30°E	17.3	2-4" Sugar Maple	N85°W	21.7
10" Maple	N37°W	34.7	Fd. Well Point Set by C.Dodt					
E.Bank Bear Creek				S08°42'E	11.95			
	N84°25'W	178'±						
S.Bank Bear Creek			Ctr. N-S B.Top County Rd.					
	N00°32'E	85'±		Due W	60'			
Ctr. E-W dirt County Rd.								
	Due S	215'±						

SIGNED BY Carl F. Roser DATE 2-26-79

STATE OF MICHIGAN — CARL F. ROSER — LAND SURVEYOR No. 12028 — REGISTERED LAND SURVEYOR

SURVEYOR'S MICHIGAN REGISTRATION NO. 12028

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY _____ DATE _____
CHIEF OF SURVEY PARTY

APPROVED AND SIGNED BY _____ DATE _____
MICHIGAN REGISTERED LAND SURVEYOR

(SEAL)

SPRINGDALE TOWNSHIP
MANISTEE COUNTY

SURVEYOR'S MICHIGAN REGISTRATION NO. _____

FORM APPROVED BY MICHIGAN STATE BOARD OF REGISTRATION, JAN. 28, 1971
REVISED MAY 14, 1975

MAY PLACE SKETCH ON BACK OR ATTACHED SHEET