LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF—:	LOCATED IN—:	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY	T. 24 N., R. 14 W.	J-7, I-9
14	T. 24 N R 14 W	14
2. PROPERTY CONTROLLING IN SECTION 23	T. 24 N., R. 14 W.	5
3. MISCELLANEOUS PROPERTY IN SECTION	T. N. S., R. E. W.	

4. LOT NO. _____, RECORDED PLAT _____

5. PRIVATE CLAIMS _____

REGISTER OF DEEDS STAMP AND FILING NUMBER

I, CARL F. ROSER, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on APRIL 20, 1982, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on _____, 19____, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

C. CONTINUED

~~A. Description of original monument and accessories and/or subsequent restoration~~:

I-9
FD. DNR MON W/BRASS CAP &
ADDED 8" ASH POST.
*18" MAPLE S70°E 77.90
* 9" ASH N10°E 62.58
9" ASH N25°W 19.3
*9" ASH S70°W 42.00

*OLD K.J.O. WITS.

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

5 ESTAB N1/8 COR ON N-S 1/4 LINE OF SEC 23 PER STD B.L.M. INSTRUCTIONS. COR FALLS IN CATTAIL AREA OF SWAMP. CUT IN TRUE LINE N & W.

J-7 RE-ESTAB N1/4 COR OF SEC 23 MIDWAY & ON LINE BETW. THE NW & NE COR'S OF S-23. SET STD. DEPT. MON. INSIDE OF 1 1/4" X 36" PIPE. COR FALLS IN TAG ALDER SWAMP. CUT IN TRUE LINE E & W.

14 ESTAB S. 1/8 COR ON E. LINE OF SEC 14 PER STD B.L.M. INSTRUCTIONS. WINDING TRAIL ROAD IS W-75'± & N-75'±. CUT IN TRUE LINE W & S.

I-9 RECOVERED DEPT MON; 1960 D.P. COR FALLS IN LARGE CATTAIL & TAG ALDER SWAMP. BEAR CREEK IS 725'± NORTH.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

5
SET 3/8" X 5/8" X 60"
IR W/RLS CAP & CED.
POST W/LOC. TAG.
6" CED N35°W 69.6
5" MAP N65°E 15.9
5" MAP. S25°E 33.8

J-7
SET DNR MON & CED. POST.
3" MAPLE S10°E 29.2
3" MAPLE S35°E 25.7
6" SWAMP ASH S85°E 35.4

14
SET 5/8" X 36" RE-ROD W/RLS
CAP & CED POST W/LOC TAG.
5" W PINE (TW) S10°W 26.6
13" W PINE S70°W 21.5
14" W PINE N28°E 3.1

SIGNED BY Carl F. Roser 05-02-83 DATE _____

SURVEYOR'S MICHIGAN REGISTRATION NO. 12028

STATE OF MICHIGAN
CARL F. ROSER
SEAL LAND SURVEYOR
No. 12028
REGISTERED LAND SURVEYOR

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY _____ DATE _____
CHIEF OF SURVEY PARTY

APPROVED AND SIGNED BY _____ DATE _____
MICHIGAN REGISTERED LAND SURVEYOR

(SEAL)

SURVEYOR'S MICHIGAN REGISTRATION NO. _____

SPRINGDALE TWP.
MANISTEE COUNTY

FORM APPROVED BY MICHIGAN STATE BOARD OF REGISTRATION, JAN. 28, 1971
REVISED MAY 14, 1975

MAY PLACE SKETCH ON BACK OR ATTACHED SHEET