LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF—:	LOCATED IN—:	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY _____	T. ____ N. S., R. ____ E. W.	
	14, T24 N R 14 W	11,12
2. PROPERTY CONTROLLING IN SECTION 23	,T. 24 N. S., R. 14 E. W.	4,1
3. MISCELLANEOUS PROPERTY IN SECTION ____	,T. ____ N. S., R. ____ E. W.	

4. LOT NO. _____ , RECORDED PLAT _____

5. PRIVATE CLAIMS _____

REGISTER OF DEEDS STAMP AND FILING NUMBER

I, CARL F. ROSER, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on APRIL 20, 19 82, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on _____, 19____, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

A. ~~Description of original monument and accessories and/or subsequent restoration.~~

C. (CONT.) 12

SET 5/8" X 36" REROD INSIDE
3/4" X 24" PIPE AND CED. POST W/LOC TAG.
6" MAP N70°E 43.5
18" MAP S25°E 15.7
11" MAP S75°W 17.1

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

4. ESTABLISH CTR OF NW1/4 OF SEC 23 PER STD B.L.M. INSTRUCTION. CUT IN TRUE LINE TO NORTH & EAST.

1 ESTAB W1/8 COR ON N. LINE OF SEC 23 PER STD B.L.M. INSTRUCTIONS. COR FALLS ON SE COR OF SWAMP. CUT IN TRUE LINE N-S-E-W. A CREEK 20'± SOUTHERLY IS 496'± EAST. FITS U.S. SURVEY.

11 ESTAB CTR OF SW1/4 OF SEC 14 PER STD B.L.M. INSTRUCTIONS. COR FALLS NEAR SE EDGE OF OPEN FIELD. CUT IN TRUE LINE E. & S.

12 ESTAB S1/8 COR ON N-S 1/4 LINE OF SEC 14 PER STD B.L.M. INSTRUCTIONS. CUT IN TRUE LINE E & W.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

4	1	11
SET 5/8" X 36" REROD INSIDE 3/4" X 24" PIPE & CED. POST W/LOC. TAG.	SET 3/4 X 48" PIPE W/RLS CAP & CED POST W/LOC TAG.	SET 5/8" X 36" REROD W/RLS CAP & CED POST W/LOC TAG.
16" MAP N20°W 37.8	8" MAP (CLUS) N40°E 14.0	8" CHERRY N45°E 12.2
16" MAP N50°E 11.8	6" MAP S50°W 29.1	7" CHERRY S25°E 53.8
10" MAP S30°E 10.4	5" MAP N40°W 12.4	10" CHERRY N35°W 67.3
15'± Creek, EAST 250'±		

SIGNED BY Carl F. Roser 05-02-83 DATE _____

SURVEYOR'S MICHIGAN REGISTRATION NO. 12028

STATE OF MICHIGAN — CARL F. ROSER — LAND SURVEYOR No. 12028 — REGISTERED LAND SURVEYOR (SEAL)

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY _____ DATE _____
CHIEF OF SURVEY PARTY

APPROVED AND SIGNED BY _____ DATE _____
MICHIGAN REGISTERED LAND SURVEYOR

(SEAL)

SPRINGDALE TWP.
MANISTEE COUNTY

SURVEYOR'S MICHIGAN REGISTRATION NO. _____

FORM APPROVED BY MICHIGAN STATE BOARD OF REGISTRATION, JAN. 28, 1971
REVISED MAY 14, 1975

MAY PLACE SKETCH ON BACK OR ATTACHED SHEET