LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF—:	LOCATED IN—:	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY	T. 24 N. S., R. 14 E. W.	H-5, G-5, I-5, K-6
2. PROPERTY CONTROLLING IN SECTION 15	T. 24 N. S., R. 14 E. W.	2
3. MISCELLANEOUS PROPERTY IN SECTION	T. N. S., R. E. W.	

4. LOT NO. _____, RECORDED PLAT _____

5. PRIVATE CLAIMS _____

REGISTER OF DEEDS STAMP AND FILING NUMBER

I, CARL F. ROSER, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on APRIL 20, 19 82, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on _____, 19____, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

C. CONTINUED

~~A. Description of original corner and accessories and/or subsequent restoration~~

I-5			K-6		
FD. R.R. SPK; REPLACED W/1 1/4" X 18" IRON.			FD 1/2" ROD; REPLACED W/DNR MON & CED POST.		
*10" W. PINE	N15°W	101.44	* 8" CEDAR	S85°E	28.77
*15" W. PINE	S60°W	61.04	*11" MAPLE	S10°W	25.90
*16" MAP (CLUS)	S15°E	52.25	* 9" MAPLE	N27°W	28.82
SET CED POST			N-S SWAMP RD.	EAST	50' ±
W/LOC TAG	SOUTH	33'	N-S RAND.	EAST	70' ±
*OLD WITS			*L. CZUBEK WITS.		

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

2 ESTAB E1/8 COR. ON N. LINE OF SEC 15 PER STD B.L.M. INSTRUCTIONS.

H-5 FD 1" PIPE IN CTR OF E-W B.TOP ROAD AS RECOVERED BY RLS, KEN ROSS IN 1979.

G-5 ACCEPTED 3/8" SPK IN CTR OF BLACK TOP ROAD (MAG PULL UNDER SPK). FITS RECORDED PLAT OF "OLD GRADE CROSSING". 16" APPLE B.T. WAS NOTED IN OLD 1960 CO. RD WITS.

I-5 FD RR SPK. IN APPROX. CTR. OF B. TOP RD. INTER. E-W-N. FITS 1955 CO. RD. COMM. WITS, SURVEY OF SEC 15 BY RLS, KEN ROSS IN 1979 AND PLAT OF "OLD GRADE CROSSING".

K-6 FD 1/2" ROD BY RLS, L. CZUBEK WHICH FITS 1970 SURVEY OF SEC 13 BY RLS, HAROLD BRUNING.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

2			H-5			G-5		
DROVE 7/8" X 18" IR. IN APPROX. CTR. OF E-W B.TOP RD.			FD 1" PIPE.			FD 3/8" SPK IN CTR OF E-W B.TOP RD.		
9" CEDAR	NORTH	40.5	*8" CEDAR	N40°E	43.13	* P. POLE	N75°E	112.38
15" CEDAR	S63°E	100.5	*8" CEDAR	N40°W	57.35	16" APPLE	S18°E	91.58
STOP SIGN POST	S32°E	46.7	*6" MAPLE	S10°E	35.38	*10" CHERRY	S63°W	89.33
SET CED POST W/LOC. TAG	S45°W	47.5	SET CED POST W/LOC TAG.	SOUTH	33'	SET CED POST W/LOC TAG	SOUTH	33'
CTR. OF GRAVEL RD. SOUTH	EAST	10' ±	*1979 ROSS WITS.			*1972 DNR WITS.		

SIGNED BY Carl F. Roser 05-02-83 DATE _____

SURVEYOR'S MICHIGAN REGISTRATION NO. 12028

STATE OF MICHIGAN CARL F. ROSER LAND SURVEYOR No. 12028 REGISTERED LAND SURVEYOR (SEAL)

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY _____ DATE _____
CHIEF OF SURVEY PARTY

APPROVED AND SIGNED BY _____ DATE _____
MICHIGAN REGISTERED LAND SURVEYOR

SPRINGDALE TWP
MANISTEE COUNTY

SURVEYOR'S MICHIGAN REGISTRATION NO. _____

FORM APPROVED BY MICHIGAN STATE BOARD OF REGISTRATION, JAN. 28, 1971
REVISED MAY 14, 1975

MAY PLACE SKETCH ON BACK OR ATTACHED SHEET