LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF—:	LOCATED IN—:	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY	T. 24 N. ~~S.~~, R. 14 ~~E.~~ W.	H-7; G-7;
2. PROPERTY CONTROLLING IN SECTION 15	,T. 24 N. ~~S.~~, R. 14 ~~E.~~ W.	15; 14
3. MISCELLANEOUS PROPERTY IN SECTION	,T. N. S., R. E. W.	

4. LOT NO. _____ , RECORDED PLAT _____

5. PRIVATE CLAIMS _____

REGISTER OF DEEDS STAMP AND FILING NUMBER

I, CARL F. ROSER, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on JANUARY 7, 1983, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on _____, 19____, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

C. CONTINUED:

~~A. Description of original monument or corner as recovered and/or established~~

15

DROVE 5/8" X 36" RE-ROD W/RLS CAP (BURIED 0.3),
P. POLE N30°W 43.72
16" MAPLE S22°W 35.4
FD SMALL R.R. IRON N78°39'07"E 14.79
SET CED POST W/LOC TAG N. 33'
CTR E-W GRAVEL RD. NORTH 5'±

14

SET 5/8" X 36" RE-ROD W/RLS CAP & CEDAR POST W/LOC TAG,
24" CHERRY S35°W 72.2
8" CHERRY N85°W 47.1
4" R. PINE N05°E 26.7

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

G-7 FD & ACCEPTED IRON BAR AS RECOVERED & USED BY KEN OSTLING IN 1960 (BUT NOT WIT. OR RECORDED) AND ALSO USED BY OTHERS (POSSIBLY KEN ROSS).

H-7 RECOVERED DEPT. BRASS CAPPED MONUMENT (K.J.O. 1960). CORNER FALLS IN APPROX. LINE WITH OLD FN. SOUTH (IN TREES & DOWN) & IN APPROX. LINE WITH CTR OF GRAVEL ROAD LOOKING WEST.

15 ESTAB. W 1/8 ON S. LINE OF SEC. 15 EQUIDISTANT & ON LINE BETWEEN SEC COR W & 1/4 COR E. OLD FN. TO NORTH IS EAST 17'±. EDGE OF HARD WOODS LINE SOUTH IS EAST 12'+

14 ESTAB. NW COR OF SW 1/4-SW1/4 OF SEC 14 PER STD B.L.M. INSTRUCTIONS. A CROOKED E-W FENCE IS NORTH 18'+. PINE PLANTATION IS NORTH 20'+.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

G-7

FD 1/2" X 1" BAR THAT HAD BEEN RAISED W/ 3/8" SPK W/RLS CAP,
*S.E. COR TWP. HALL N50°W 70.9
*12" R. PINE N43°E 41.71
*P. POLE S50°W 75.36
CTR N-S B. TOP RD. EAST 1'±
CTR E-W GRAVEL RD. SOUTH 2'±

H-7

FD DNR MON. - ADDED CEDAR POST.
* 7" J. PINE N50°W 43.8
*18" MAPLE S15°E 8.8
* 7" CHERRY N15°E 81.8

* = KJO 1960 B.T.'s (still standing)

SIGNED BY Carl F. Roser 05-02-83 DATE _____

SURVEYOR'S MICHIGAN REGISTRATION NO. #12028

STATE OF MICHIGAN (SEAL) CARL F. ROSER LAND SURVEYOR No. 12028 REGISTERED LAND SURVEYOR

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY _____ DATE _____
CHIEF OF SURVEY PARTY

APPROVED AND SIGNED BY _____ DATE _____
MICHIGAN REGISTERED LAND SURVEYOR

(SEAL)

SURVEYOR'S MICHIGAN REGISTRATION NO. _____

Springdale Twp.
MANISTEE COUNTY

FORM APPROVED BY MICHIGAN STATE BOARD OF REGISTRATION, JAN. 28, 1971
REVISED MAY 14, 1975

MAY PLACE SKETCH ON BACK OR ATTACHED SHEET