LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF—:	LOCATED IN—:	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY	T. 24 N. S., R. 14 E. W.	I-6; H-6; K-9;
2. PROPERTY CONTROLLING IN SECTION 15	,T. 24 N. S., R. 14 E. W.	13
3. MISCELLANEOUS PROPERTY IN SECTION	,T. N. S., R. E. W.	

4. LOT NO. _____ , RECORDED PLAT _____

5. PRIVATE CLAIMS _____

REGISTER OF DEEDS STAMP AND FILING NUMBER

I, CARL F. ROSER, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on JANUARY 7, 1983, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on _____, 19____, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

~~A. Description of corner evidence found and/or method applied in restoring or re-establishing corner:~~

C. CONTINUED

13

SET 5/8" X 36" RE-ROD W/RLS
CAP & CEDAR POST W/LOC TAG.
P. POLE N40°W 70.77
RR TELEPHONE POLE N55°E 54.70
5" R. PINE S73°E 76.50
CTR GRAVEL ROAD West 120'±
(IN CURVE)

K-9

FD DNR MON - ADDED CEDAR POST.
* 30" B. CHERRY S55°W 49.8
* 23" B. CHERRY S67°E 50.5
9" B. CHERRY N22°E 77.9

* = KJO 1960 BT'S.

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

I-6 FD 2" PIPE FOR E 1/4 COR OF SEC 15 AS RECOVERED & ACCEPTED BY RLS, KEN ROSS IN HIS SURVEY OF THE SW 1/4 OF THE NE 1/4 OF SEC 15 IN 1979. COR FALLS IN LARGE OPEN MARSH. A N-S FENCE IS 5' EAST.

H-6 FD & ACCEPTED 3/8" ROD BY RLS, KEN ROSS AS ESTABLISHED BY KEN AT INTERSECTION OF ONE-QUARTER LINES IN HIS SURVEY OF SEC 15 IN 1979.

13 ESTABLISHED CTR OF SE 1/4 OF SEC 15 PER STD B.L.M. INSTRUCTIONS. A FENCE COR (FN'S S&E) IS 6'± EAST & 20'± SOUTH. CTR OF R.R. TRACKS (NE & SW) IS 28.2' WEST & 36.3' NORTH.

K-9 RECOVERED DEPT. MON. AS ESTABLISHED BY DOUBLE PROPORTION BY DEPT. RLS, KEN OSTLING IN 1960.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

I-6

FD 2" PIPE & SET DNR MON
INSIDE PIPE - ADDED CEDAR
POST W/LOC TAG.
12" W. PINE S74°W 172.0
7" W. PINE S40°W 190.3
℄ R.R. TRACKS WEST 445'(±2')

H-6

FD 3/8" ROD W/CAP #17634 &
ADDED CEDAR POST W/LOC TAG.
20" CHERRY N60°E 133.4
22" CHERRY N78°E 161.8
6" W. PINE N32°W 50.4

SIGNED BY Carl F. Roser 05-02-83 DATE _____

STATE OF MICHIGAN — CARL F. ROSER — LAND SURVEYOR No. 12028 — REGISTERED LAND SURVEYOR (SEAL)

SURVEYOR'S MICHIGAN REGISTRATION NO. #12028

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY _____ DATE _____
CHIEF OF SURVEY PARTY

APPROVED AND SIGNED BY _____ DATE _____
MICHIGAN REGISTERED LAND SURVEYOR

(SEAL)

SURVEYOR'S MICHIGAN REGISTRATION NO. _____

SPRINGDALE TWP.
MANISTEE COUNTY

FORM APPROVED BY MICHIGAN STATE BOARD OF REGISTRATION, JAN. 28, 1971
REVISED MAY 14, 1975

MAY PLACE SKETCH ON BACK OR ATTACHED SHEET