FEB 0 g 2000

0 2000			RECORDATION									
SECTION	Filing R	lequirem	ent of Act 74, N	Ոich <del>. P</del>	·.A1	970 —	FILE	)				
For corners in Mason	Located In:		Corner Code #	AT	1 1	19	0'CL0	CK	9	M		
(County)												
1. Public Land Survey	T 17N R 15	<u>w</u> 	<u>I-11</u>					1999 1881 E1		-		
Property Controlling S     in Section S      Miscellaneous	T R T R T R T R S T	  R					SON C STER O	OUNTY IF DEED	os	& File	Numbe	÷r
Property in Sec. S	TR	_		<del></del>								
4. Lot No, Recorded 5. Private Claims	J Plat					1	A B	C D	E F (	3 H	J K	L N
5. Private Claims						2	-6	5	4	3	2	1
i, Kenneth L. Ross	, in	a field sun	vey on May 22, 1999	1		3 4	7	8	9	10	1.1	1.2
do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:  NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.				5 6 7	18	17	16	15	14	13		
				8 9	19	20	21	22	23	24		
				10 11	30	29	28	27	26	25		
A. Description of original montions I-11, Corner Common to S	ument and access actions 26,27	sories and	i/or subsequent res 35, T.17N., F	storatio	on:	12 13	31	32	33	34	35	36
GLO, John Hodgson 4th quarter, 1838 Set Post common to Secs. 26, (1) Maple, 18", S53°E, 22 li (2) Hemlock, 18", N42°W, 22	April, 1967, Act 132, K.L. Ross, "Ex. 4" pipe" (3) P.P. N89°W, 68.50' (5) White Oak, 24", N31°E, 59.30' Distance North to I-10, Not Given.				K.I Wi	October, 1998, Act 132 K.L. Ross, "Existing 14" iron" Witness (5) Given (6) P.P. S68°W, 74.85'						
May, 1901, Book 2, Page 126		June,	1990, Act 132						12", Monume			
And Book 4, Page 38, R.O. Towns "found stake", No Witnesses Distance West to H-11, 2647.92' Distance South to H-12, 2625.48'  1968 Mason County Road Commission "3/4" iron pipe		K.L. Ross, "Ex. %" pipe" Witnesses (3) & (5)  December, 1993, Act 132, K.L. Ross, "ex. Capped 1ron" No Witnesses Given Distance North to I-10, 2644.78'					18"		e Whit		_	
<ul> <li>(3) P.P. West, 68.2'</li> <li>(4) Twin Oak, 36", NE, 97.2'</li> <li>B. Description of corner evide</li> </ul>	ence found and/or	method	applied in restoring	or ree	stablis	hing cor	ner:		٠			
I-11, Corner Common to S Found %" iron re-rod and Stc East and West. Witnesses (I I found no other evidence to	one, Center-line	e of Tay: e been d	lor Road, 6" bel estroyed. Witne	ow the	top	of the q ru (9) a	gravel Are st	surf.	ace. )	Fence in goo	Line t d cond	o the
												.~
C. Description of monument I-11, Corner Common to S						ing the p	ositio	n of th	e come	er:		
I replaced the '4" iron re- below the gravel surface of west ot the Cast Iron Harris	Campbell Road.	I left	the stone in pla	ce 1.5	' bel	ow the	top o	f the	Gravel lence	surf	e pos	d jus

- (5) 26" White Oak, existing 60d spike, NW side, N33°E, 59.30'
- (6) P.P. existing 60d spike NW side,  $568^{\circ}W$ ,  $74.85^{\circ}$
- (7) Red Pine, 12", existing 60d spike, SW side, N45°W, 44.80'
- (8) Reinforced Concrete Monument, S84°E, 33.00'
- (9) Triple White Oak, 18" at base, existing 60d spike, SW side, \$30°E, 48.90'

Signed by\_ Surveyor's Michigan License No. 17634 Date

chigan state board of land surveyors, Jan. 29, 197 REVISED MAY 14, 187 REVISED MAY 14, 187 REVISED JAN., 198: Adapted for word processing march, 199:  $4\,\text{PAGE}\,\,253$ 

LAND

SURVEYOR No. 763

LIBER

Peer Group Reviewed
and Approved
2-14-49
Kenneth L. Ross