SURVEY & REMONUMENTATION

APR 2 8 1995

CO	RAR	115	123	ON
	IVI	411	フェフル	1 1 1 1 3

LAND CORNER RECORDATION CERTIFICATE

IN LAND CORNE	R RECORDATION CERTIFICAT	FILED
Filing Require	ement of Act 74, Mich. P.A. 197	O AT 10:35 O'CLOCK a N
Located In:	Corner Code ##	
		OCT 3 1994
T <u>18N</u> R 15W. T R T R	E-6.	MARY GOLDEN KOLASKI MASON COUNTY
S T R S T R S T R S T R	R	REGISTER OF DE
ecorded Plat		
		2 6 5 4 3 2
to a state annual and Associate	10. 0 lk	4 7 3 9 10 11 12 12 15 15 15 15 15 15 15 15 15 15 15 15 15
e-established, monumented, re-m	nonumented, recovered, found as	9 28 27 26 25
blished in 1838 by Sibley. th the following corner results of the S13°W 32 lks. N22°E 11 lks. found stake and planted an ps. The following corner S13°W 34 lks. N16°E 41 lks. t. 16 South 39.90 chains t. 16 North 40.44 chains 40 & 141). idence found and/or method a box with spike over railrund the following corner rection 16 bears North 2666	In 1958, Steph POT. No refer In 1974, Ross iron in monume bears S0°06'29 In 1977, Clint (see LCRC book references: 7. Power Pole (2669.0') 8. Power Pole 9. Anchor Pole spolled in restoring or reestablishin road spike which was inside eferences: 8.80 ft.	N46°W 50.00 ft. e S32°W 70.45 ft. CONTINUE ON BACK
	Filing Require Located In: T18NR 15W	Filing Requirement of Act 74, Mich. P.A. 197 Located In: Corner Code ## T 18N R 15W E-6. T R T R T R S T R

Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Replaced spike & railroad spike with a 5/8"X2' rerod inside the pipe and on top of rerod placed a County aluminum cap stamped to identify the corner. The following new corner references:

SW corner of metal bldg. N17°43'E 285.73 ft.

Center line of railroad and

Hwy. US-10

East 270.81 ft.

S47°E 191.54 ft.

Power pole

270.81 ft. 191.54 ft. 54.62 ft. 110.80 ft. S47°E N53°E

Power pole

NE corner of metal bldg.

(Monte's Auto Service)

S13°18'W

AND S Date Oct. 5, 1994 Signed by Surveyor Michigan License No. RLS-30894

Peer Group Reviewed and Approved

FORM APPROVED BY MICHIGAN STATE BOARD OF LAND SURVEYORS, JAN. 28, 1971 REVISED MAY 14, 1975

REVISED JAN., 1983

WICH! OF MICHIGA

JOHN C. Schulke

LAND

No. 30594

Kenneth L. Ross Mason County Surveyor

LIBER

3PAGE 189

E-6 segil

continuing column "A"

Undated, Mason County Road Commission found L iron at the corner. The following corner references:

10. 14" Oak N57°E 54.3 ft.

11. 12" Oak N70°E 81.9 ft.

12. 10" POP S39°E 88.5 ft.

13. Power Pole N69°W 98.0 ft.

In 1953, MDOT indicated angle iron and placed a monument box. The following corner references that MDOT list:
10" Poplar
12" Oak
14" Oak
Power Pole

N57°E
14.32 ft.
Power Pole

N69°W
98.04 ft.