## LAND CORNER RECORDATION CERTIFICATE

CHOTION	F	iling Require	ment of Act 74, Mich	. P.A <u>. 19</u>	70			<del></del>	٦
For corners in					FILED				
Mason (County)	Located	ln:	Corner Code #	AT.	3:04	0'CLOC	<u> </u>	P_ N	٨
Public Land Survey	т <u> </u>	R_17W_ R R	I-7	-	NO	ov 2.1.		``   	
Property Controlling     in Section     Miscellaneous		R R T R		- - -	M/	ASON CO STER OF	UNTY DEEDS		nber
Property in Sec.	ST	R		_		_			
4. Lot No, F	Recorded Plat				1 A B	C D E	F G	<u>н</u> I Ј	K L
					26.	5	4	3 2	1
I, Kenneth L. Ross do hereby certify that under in in lines 1 and 2 above were	requirements of P.A. 7	4, Michigan P.A.	of 1970, the corner points m	entioned	4 7 5	8		10 11	_
current manual of survey inst Management or by a decree of above were in conformance v	tructions of the United of a Court of Law and/o with the rules of the M	States Departn or that the cornel lichigan Board o	nent of the Interior, Bureau r points mentioned in lines 3, i Land Surveyors or by a Dec	of Land 4 and 5 cree of a	6 18 7 8 19			15 14 22 2	
Court of Law; established expressed below:	, re-established, mo	onumented, re-n	nonumented, recovered, fo	und as	9 10 30	-   :		27 20	
NOTE: Not more than 4 on this certificat		same town a	nd range, may be record	ied	11 30			34 39	
			ind/or subsequent restor	ration:	13	32		34 3	3 30
On October 17, excavation, I found a 36" below the road sucorner.	e to 1839 itnesses  r, 1891 ntified by t Stake. n. 2597.76' , 2603.37'  er evidence found to Sections 14,1  1998, I found to large spike wit rface. I left t	Book 1, Page No new Witner Distance West Distance South France South F	tt to H-7, 2637.69' tth to I-8, 2628.78' toss, PLS, Act 132, u iron rod. e, N51°W, 66.34' e Pine, S25°W, 89.55' ock S50°E, 89.98' tt to J-7, 2617.38' th to I-6, 2627.44' tth to I-8, 2606.53' d applied in restoring or T.19N., R.17W., cod as described by R sher, 12" long as a 1	nrecorded reestablish oss, it m riser for no other e	ing Corner: easured 18: a 1 %" pip evidence to	" Long, ' e that w	as foun the lo	d to be cation	of thi
I replaced the (MASON COUNTY MONUMEN as a careful and fait Ext. "BT" (1) 15" Map. Ext. "BT" (2) 5" White Ext. "BT" (3) 12" Hem. (4) Large Clump of M	to Sections 14,1  c 'w' iron rod and T) place on top hful re-establis le, N51°W, 66.30° e Pine, S25°W, 89 lock, S50°E, 89.3 aples, N66°E, 37	d large spike of the 1 4" hment of the ', (60d spike 9.64', (60d spike 90', (6	e in the exact location pipe and 12" below the position of the original position of the original pipe.  Expire in SE side)  ike in NE side)	on, with ne surface	a Harrison of the ro	Cast Ir	on Monur S Corne OF KENNETH LA SURV	MICH L. ROSS ND EYOR	tamped:cepted
Surveyor's Michigan Lice	ense No. 17634			FORM	APPROVED BY MIC	HIGAN STATE			AMAY 14, 16 SM JAN., 1 MARCH: 1
Approved by Peer Review C Kenneth L. Ross, County R	Group On epresentative	9-98	Africa			AUMF	- <i> </i>	Itiliza.	