LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF—:	LOCATED IN—:	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY	T. 14 N. ~~S.~~, R. 9 E. ~~W.~~	C-4, C-3
2. PROPERTY CONTROLLING IN SECTION 8	,T. 14 N. ~~S.~~, R. 9 E. ~~W.~~	10,3
3. MISCELLANEOUS PROPERTY IN SECTION	,T. N. S., R. E. W.	

4. LOT NO. _____ , RECORDED PLAT _____

5. PRIVATE CLAIMS _____

REGISTER OF DEEDS STAMP AND FILING NUMBER

I, Kenneth J. Ostling, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on August 7, 1980, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on _____, 19____, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

A. Description of original monument and accessories and/or subsequent restoration:

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

C-4 Set corner by single proportionate measurement between section corners, according to data returned in the U.S. examination of 1854 by Brewer. No previous corner found.
10 Set by standard survey procedure for the subdivision of sections.
3 Set by standard survey procedure for the subdivision of sections.
C-3 Set corner in E-W fireline - pipeline at record measure from stream south and west. Unable to locate previous corner because of pipeline construction.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

C-4
Set DNR Mon. & Ced Post
5" W. Pine N40°E 32.6'
13" W. Oak S35°E 30.1'
4" R. Oak S85°W 20.7'

10
Set 5/8" x 34" re-rod w/RLS cap & Cedar Post w/loc tag
8" Blk. Cherry N85°W 17.6'
2" Maple N20°W 2.0'
9" Red Oak S80°E 18.3'

C-3
Set DNR Mon & Ced Post
6" Hemlock Due N 23.4'
9" Hemlock S20°E 17.1'
8" Hemlock S60°W 25.0'
11" S. Maple N10°W 54.7'
1 1/2" Creek Due W 240±4"

3
Set 5/8" x 34" re-rod w/RLS cap & ced post w/loc tag
5" Maple N75°E 5.6'
9" W. Oak N85°W 19.4'

SIGNED BY Kenneth J. Ostling DATE 10/16/80

STATE OF MICHIGAN KENNETH J. OSTLING LAND SURVEYOR No. 10068 REGISTERED LAND SURVEYOR

SURVEYOR'S MICHIGAN REGISTRATION NO. 10068

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY _____ DATE _____
CHIEF OF SURVEY PARTY

APPROVED AND SIGNED BY _____ DATE _____
MICHIGAN REGISTERED LAND SURVEYOR

(SEAL)

SURVEYOR'S MICHIGAN REGISTRATION NO. _____ MECOSTA COUNTY

FORM APPROVED BY MICHIGAN STATE BOARD OF REGISTRATION, JAN. 28, 1971
REVISED MAY 14, 1975

MAY PLACE SKETCH ON BACK OR ATTACHED SHEET