MECOSTA COUNTY REMONUMENTATION PORGRAM

CORNER APPROVED BY PEER GROUP ON NOVEMBER 4, 1993.

LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. P.A. 1970

For corners in	l l	C C #	1	CTÁT	E OF MICHIGAN	•	
MECOSTA (County)	Located In:	Corner Code #		COUN	TY OF MEDOST	A	
Public Land Survey	T <u>15N</u> R 09W	K-13		RE GER	VEO FOR RECO	(I)	
•	T R		- 1	' 96 Ji	AN 16 A10	.4.2	
	T R		.	<i>)</i> U 06	NIA OI MI	(1)	
	T R		•	د مسر			
	T R T R	<u>_</u> _	-	(Jan.	m Brown		
	T R		·		ds Stamb & I		
	T R		- Keg	ister of Dee	eus Stampreri	-iie Mumbe	er
• •				-			
4 Lot No, Recorded F 5. Private Claims			****	A B C	DEFG	HIJK	K L N
o. Trivate orantis				2	5 /	9 9	1
				3	7 7		1
I, JAMES G. KNAPP	in a field survey.	on NOVEMBED 1	1003	4 7	8 9	10 11	12
do hereby certify that under require				5			
mentioned in lines 1 and 2 above we				6 - 18 -	17 16	15 14	13
required in the current manual of standard in the current manual of standard management of the current manual of standard man				7			
mentioned in lines 3, 4 and 5 above w				8 - 19	20 21	22 23	. 24
Land Surveyors or by a Decree of a Coure-monumented, recovered, found as	· ·	d, re-established,	monumentea,	9			-
	•			10 30	29 28	27 26	25
NOTE: Only one corner may be rec	orded on this certificat	ρ		11			-
no in any one come may be re-				12 31	32 33	34 35	36
A. Description of original monur DEPUTY SURVEYOR, JOHN HODGSON,				1313	2640 AO 6000	EDOM COL	
1/4 CORNER SECTION 36 AND WITH		BEECH 8" N53°		(28.38 FE		FROM SOD	111
	!	BEECH 8" N59°	w 15 LINKS	(9.90 FE	ET)		
FIELD BOOK No. 1, PAGES 40 THR	U 47 AT THE REGISTER	OF DEEDS OFFICE	SHOW THE FOR	LLOWING NO	res by L. W.	JUNE,	
COUNTY SURVEYOR, IN 1895, WHILE	· ·						
	PINE STUMP PINE STUMP			(25.08 FEET (37.62 FEET	=	٠	
		10 535 1	J. 221KD		.,,		
MECOSTA COUNTY ROAD COMMISSION CORNER AS "TILE AND CHARCOAL",							
T14N-R9W.						-,,	•
A CERTIFICATE OF SURVEY BY THO	MAS J. MUELLER, P.S.	25861, RECORDE	IN LIBER 10	, PAGES 78	4 AND 785, O	N OCT. 23	, 1979
NOTES CORNER AS, "FOUND 5/8" I	RON".	-					
A LAND CORNER RECORDATION CERT	IFICATE BY THOMAS J.	MUELLER P.S. 25	861, RECORDE	D IN LIBER	1, PAGE 524	, ON OCTO	BER
23, 1979, NOTES CORNER AS, "FD		RLINE TO NORTH	ND CENTERLIN	E TO WEST,	111.36' EAS	To Thanking	23m
IRON W/R.L.S. CAP", AND WITNESS	164 200	LAR N74°	E 13.41'		TITUTE .	E BY MICH	A BA
APPROVED BY MECOSTA CO. PEER (IN ACCORDANCE WITH P.A. 345 of 19	GKUUP				All *	•••	
d n	16" TRI	PLE MAPLE S82°			# !	JAMES G.	*
CHAIRMAN MAJOR	3" POPL	AR S65°	W 33.55	3.4		emapp Land Survens	2 4
DATE NOV. 4. 199	3					Ba.	S.
						25853	. 446,0
B. Description of corner evidence FOUND 1/2" X 15" IRON ROD IN A	e found and/or method	applied in restoria "	ng or reestablis איניא פארוניאס איניין	shing corner	CHARCOAL BY	ALA LINO	The Charles
BELOW GROUND SURFACE AND EXTEN							GRAVE
NORTH AND 12 MILE ROAD (24' GR					GRAVEL) SO	UTH.	
FOUND REMAINS OF PINE STUMP S3.	5°E, 37.6 FEET AS NO	red by L. W. Jun	E, IN 1895 NO	TES.			•
C. Description of monument for	corner and accessories	s established to pe	rpetuate locati	ing the posi	tion of the co	rner:	
K-13 - SECTION CORNER COMMON TO FOUND 1/2" X 15" IRON ROD IN A			ec w/ouspoost	33m TC 30	CENTED AC A	ANDERUT N	NTD.
FAITHFUL PERPETUATION OF THE P		,	S W/CHARCOAL	AND IS AC	CEPTED AS A	CAREFUL A	רואד
REMOVED 1/2" X 15" IRON AND 2		et in the same <i>i</i>	STANDARD ME	COSTA COUN	IY REMONUMEN	TATION	
MONUMENT W/ONE TILE ON SLEEVE OF SET 60p SPIKE W/REMONUMENTATION		OF 7" WHITE CAR	:	AZ. 1	0°, 49.35	FERT	
SET 60p SPIKE W/REMONUMENTATION			=	AZ. 76°	-	FEET (O.B	.T.)
SET 60p SPIKE W/REMONUMENTATIO	N TAG IN WEST SIDE	OF 6" RED OAK			5°, 123.62	FEET	
SET 60p SPIKE W/REMONUMENTATION	N TAG IN N.E. SIDE	OF 32" MAPLE		AZ. 33	9°, 125.20	FERT	
	<i>()</i>						
Signed by AMUS I	. Knows		ate .T	anuarv 19	. 1995		
Signed by Surveyor's Michigan License No.	25252						
ourveyor s wiichigan License No	45853		FORM APP	ROVED BY MICHIGA	IN STATE BOARD OF L		, JAN. 28, 1