SURVEY & REMONUMENTATION

APR 0 4 1996

COMMISSION

MECOSTA COUNTY REMONUMENTATION PROGRAM

CORNER APPROVED BY PEER GROUP ON MAY 18,1995

LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. P.A. 1970

Joanne Brown
Register of Deeds
Mecosta County

'95 NOV -2 A11 :13

Register of Deeds Stamp & File Number

For corners in Mecosta (County) Sec 15 Located In:

				Corner Code
1. Public Land Survey		T 15N	R 7W	G-5
		T	R	
		T	R	
		T	R	
2. Property Controlling	S	T	R	
in Section	S	T	R	
3. Miscellaneous	S	T	R	
Property in Sec.	S	T	R	

4. Lot No. _____, Recorded Plat _____
5. Private Claims _____

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2		6		5		4		3		2		1	
3													
4		7		8		9		10		11		12	
5													
6		18		17		16		15		14		13	
7													
8		19		20		21		22		23		24	
9													
10		30		29		28		27		26		25	
11													
12		31		32		33		34		35		36	
13													

I, James J. Keller, in a field survey on January 19 19 95, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

1839 Noah Brookfield, GLO, Set post cor 9-10-15-16; Beech 14 N65°W 21 Links
Sugar 10" S67°E 30 Links
1895-96 Lyman W. June, Fence Post N80°W 50 Links; Apple 7" S50°W 88 1\2 Links
1940 M-66 Road Plans Project. 54-23 Road Plans
Sept. 1 1977 Gray #17741 (LCRC L1-P332) Found Bolt
N75°E 91.6' 36" Hazel Nut; S70°W 40.4' 12" Hazelnut
S55°W 61.2' 18" Hazelnut

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Jan 19,1995, James J. Keller Found 1" Drag tooth 0.90' long in centerline M-66 & 16 Mile Rd. Excavated to a depth of 3.0' finding no further evidence.
Set 30d NE Side 8" Sassafras N43°W 48.12'
NW Corner culvert headwall N68°E 45.08'
SW Corner culvert headwall S56°E 44.33'
Set 30d 8" Ash S67°W 43.73'

APPROVED BY MECOSTA CO. PEER GROUP
IN ACCORDANCE WITH P.A. 345 of 1990
James J. Knapp
CHAIRMAN
DATE MAY 18, 1995

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:
Set Remonumentation Monument and is accepted as a careful and faithful perpetuation of the position of the original corner.

Set 30d and tag NE Side 8" Sassafras N43°W 48.12'
NW Corner culvert headwall N68°E 45.08'
SW Corner culvert headwall S56°E 44.33'
Set 30d and tag 8" Ash S67°W 43.73'

STATE OF MICHIGAN
JAMES J. KELLER
LAND SURVEYOR
No. 10693
REGISTERED LAND SURVEYOR

Signed by James J Keller Date 27 June 1995

Surveyor's Michigan License No. 10693

FORM APPROVED BY MICHIGAN STATE BOARD OF LAND SURVEYORS, JAN. 28, 1971
REVISED MAY 14, 1975
REVISED JAN., 1983
ADAPTED FOR WORD PROCESSING MARCH, 1993