LAND CORNER RECORDATION CERTIFICATE FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF -:	LOCATED IN-:	CORNER CODE NUMBER	1 100
1. PUBLIC LAND SURVEY	26 T. 5 S., R. 10 K.	1-10, K-10	Nonco
2. PROPERTY CONTROLL- ING IN SECTION—	26 ,T. 5 S., R. 10 E.	·	
	, T N. R E. W.		
4. LOT NO, R	ECORDED PLAT		
5. PRIVATE CLAIMS			REGISTER OF DEEDS STAMP AND
I, Dwayne Scott the corner points mentioned i	in lines 1 and 2 above were, in a	rtify that under requirements of field survey on December	of P.A. 74 Michigan P.A. of 107

the corner points mentioned in lines 1 and 2 above were, in a field survey on December , 19 75, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on December , 19 75, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

A. Description of original monument and accessories and/or subsequent restoration:

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

K-10
4" dia. Iron pipe
filled with concrete and aluminum cap
Corner is approximately 90.'
N.W. of dike inter. and 0.5' above
water surface