LAND CORNER RECORDATION CERTIFICATE FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF -:	LOCATED IN -:	CORNER CODE NUMBER	1
1. PUBLIC LAND SURVEY	26 T. 5 S., R. 10 E.	1-10, K-10	
2. PROPERTY CONTROLL- ING IN SECTION—	26 ,T. 5 K. R. 10 E.		
3. MISCELLANEOUS PROPERTY IN SECTION—	, T		
4. LOT NO, REC	CORDED PLAT		
5. PRIVATE CLAIMS	·		REGISTER OF DEEDS STAMP AND FILING NUMBER
re-established, monumented, re and rules therefore as required Bureau of Land Management of and 5 above were, in a field sur-	inner I and X above were, in a monumented, recovered or rein the current manual of surver by a decree of a court of law.	stored as expressed below and sy instructions of the United S. Furthermore, that the corne 19.75, found, recovered, res.	of P.A. 74, Michigan P.A. of 1975, established in conformance with regulation states Department of the Interior points mentioned in lines 3, tored, established or re-establish ration for Land Surveyors or, by
			•
A. Description of original mon	ument and accessories and/or s	ubsequent restoration;	•
		•	
•			
•	•		
	•		
B. Description of corner eviden	ne found and for mathed analis	od in masteriae on an antablishin	•
1-10	re round surrior method ships	K-10	g corner;
Rec. 5/8" Iron re E-W. Fence line	od in old		e filled with concrete
	-		
	•		
C. Description of monument for	corner and accessories establis	hed to perpetuate locating the	position of the corner:
1-10		K-10	
	" Oak P.K. & Tag " Ach P.K. & Tag	4" dia. Iron pipe filled with concrete Corner is approximat	and aluminum cap
S. 45°W. 0.50' Fa	ce of burned stump	N.W. of dike inter.	and 0.5' above

water surface

22" Oak P.K. & Tag 38" Ach P.K. & Tag Face of burned stump approximately 8' high