DEC 19 2000

MONTCALM COUNTY REMONUMENTATION PROGRAM

SECTION

LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. P.A. 1970

Mo	ontcalm	Locate	ed In:	Corner Code #	!		. [STA	E OF	IICHIGA	N		
(County)		Ricomer	Bloomer Township					1101	MONTCALM COUNTY RECORDED				
		Biootilet	TOWNSIAD		-		:	n Kali		.55 .9:12:5	שמ"ל		
						,							
1. Public Land Survey Sec. 4, 5 T 09 N R 05 W E-02								L(REG	ORI A. ISTER (WILSON DE CEED	S		
		<u>T</u>	R	<u> </u>			L		<u> </u>		<u>.T</u>		
		T											
2	Property Controlling	s '	R R										
	in Section	s T	_ <u>R</u>			egiste	of D	eeds S	tamp &	& File I	Numbe	er	
	Miscellaneous	ST_	_ R		 -								
ı	Property in Sec.	S T	R										
4 1	ot No.	Population Dist											
5 F	Private Claims	Recorded Flat				1 A	В (C D	E F (ЭН	i J K	L N	
						2		5	4	3	. 2	1	
						3		5	4	3	2	1	
i.	William G. Tin	alev	in a field	sun/ev on June	13 2000	4	-		_	10	- ,,		
do I	hereby certify that unde	r requirements of P	.A. 74, Michigan	survey on June P.A. of 1970, the corne	r points mentioned	5	7	-8	9	10	11	12	
in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land											-		
Man	agement or by a decree	e of a Court of Law	and/or that the	corner points mentioned	in lines 3, 4 and 5	6	18	17	16	15	14	13	
abor	ve were in conformance	e with the rules of t	he Michigan Be	pard of Land Surveyors	or by a Decree of a	7	70			-			
	π or Law; establishe ressed below:	ea, re-establishea,	monumented,	re-monumented, reco	vered, found as	8	19	20	21	22	23	24	
•						9					į.		
NO.	TE: Not more than on this certifica		the same tow	n and range, may be	recorded	10	30	29	·· 28· ·	27	26-	25	
	On this certifica	ate.				11			········		:	- ·	
						12	31	32	33	34	35	36	
Α.	Description of origin	al monument and	accessories a	ind/or subsequent res	toration:	13 L				L	L		
1.		1, Orange Risdo Set ¼ section pos		veyor, GLO notes, N	orth between Se	ctions	4 and	5					
		igar 14"	S47°E	5 links (3.30 fee	t)								
		igar 14"	N47°W	55 links (36.30 fee									
2.	No date. Salisbury	and Sanders S	urvey for Con	sumers Power Com	nany at Tingley a	nd Acc	oniat	oo offi	~~				
	Meet 1/2 corne	r Section A. Comi	sutad (prorata	dietance on etraight	linal not 1/" mina a	A		المام الكاكا		iterline.	Dista	nce	
	To SW corner	Section 4 is 2645	i.14 feet and t	o NW comer of Section	n 4 is 2569.74 fee	ם בי הבים אי	V THE	MONTO	ALM CC	MINITY (י חמיים	
		oak 12" lephone pole		35.40 feet 43.50 feet	GROL	JP AS 1	HE OF	FICIAL	CORNE	R UND	ER MICI	HIGAN	
		wer pole	S80°E	44.00 feet	PUBLI	C ACT 3	45 OF 1	990 AT	A MEET	NG HEL	D <i>/0/1</i>	100.	
		·				٠		1	15	J			
		•						Willi	am Tingl	ey, PS, (Chairman	1	
В.	Description of corne	r evidence found	and/or method	applied in restoring o	r reestablishing co	mer:	``		•	•			
	Searched the appa	rent location of	the original of	corner, excavated 4.	00 feet x 5.00 fee	t x 4.0	0 fee	t deep	. Fou	nd ½"	iron p	ipe at	
	distance fits GLO	nd no otner evid distances. The 1	ience. Kecn " iron nine v	ecked the distance as in line with T10N	to E-03 as 2645. -R05 F-13 instead	14 teet	tand oN_pr	to E-0	1 as 2	2569.7°	1 feet.	This	
:	west of centerline	of road. Salisbu	y pipe was 2	0 feet west of center	line of road.	101 10	314-170	OW L.	VI. 146	sw boi	IIL 15 4.	v ieet	
_	B. adam	4.6					4						
C.	Set remonumentati	inentior comer a:	iu accessorie: iument hox ii	s established to perpe n true line between T	tuate locating the	position	of the	Corne			مدمناسط	nee	
	Set N/T SE/S	6 4" tree	S38°W	53.95 feet	0014-110011 E-01 6	inu ro	/I 1- I\U	344 E-1	at b	C OF	MIC.	nce.	
	Set N/T NE/S		S07°E	220.74 feet					All Haring	E OF	-71/6	P. Cal	
	Fnd PK NE/S		S71°E	45.38 feet				É	The state of the	• Willi	•	2	
	Distance to E	'S power pole -₋01	N13°E North	295.76 feet 2569.71 feet				HIII.	^		LEY	**	
	Distance to E		South	2645.14 feet				Ę	6	PROFES SURV	SSIONAL EYOR	× ×	
								16600		N	0.	. 2	
This	s corner is accented	as the careful a	nd faithful rec	stablishment of the	nacitian of the a	iainal :	00 HM -		William Co.	**	104	SILVER NO.	
					_	•			TOU.	ROFES!			
Bea	rings given are mag	netic. Standard	remonument	ation pipe consists o	of a Berntsen stai	nless s	steel 2	2 3/8" >	(30" p	ipe W	Ha br	ass	
cap	stamped "MONTCA	LM COUNTY RE	MONUMENTA	ATION, P.S. # 30104"					•				
			_				÷						
C:	00/. 1 value		7	B.e.	15/	1/00	•						
Sign	ied by www.	on a	maju	Date Date	10//	1100	<u> </u>						
Surv	reyor's Michigan Licer	nse No	30104	1	FORM APP	ROVED BY	MICHIGA	N STATE BO	DARD OF L				
										R	YAM CBBIVE L DSSIVER	/ 14, 1975 AN., 1983	
								ADAPT	ED FOR WO	PROCE	BSING MAF	(CH, 1993	





PAGE 283