## MONTCALM COUNTY REMONUMENTATION PROGRAM

## LAND CORNER RECORDATION CERTIFICATE

## Filing Requirement of Act 74, Mich. P.A. 1970

SECTION

For corners in Montcalm	Located In:	Corner Code #		STATE OF	MICHIGA	N		
(County)	- Winfield Township			REC	m county Orded			
			7	NOV 2000	9:12:5	7 AM		
1. Public Land Survey Sec	TR TR	J-11		LORI A REGISTER	WILSON OF DEED	<u>s</u>		
in Section S 3. Miscellaneous S	T R R S T R R S T R R S T R R S T R R S T R R S T R R S T R S T R S T R S T R S T R S T R S T R T R		Register	of Deeds	Stamp &	& File !	Numbe	r
Property in Sec. S	6 T R							
4. Lot No, Rec	orded Plat		, A	B C D	E F	G H	ΙJΚ	L M
5. Private Claims				į	4	3		ei,
		•	3 _	3	- 4		<u> </u>	
I. William G. Tingle do hereby certify that under re	∋y , in a field s equirements of P.A. 74, Michigan	survey on July 20,2000 P.A. of 1970, the corner points me	o , 4 entioned 5	7 8	9	10	11	12
in lines 1 and 2 above were in current manual of survey instru	in conformance with regulations uctions of the United States Dep	s and rules therefore as require partment of the Interior, Bureau o corner points mentioned in lines 3,	d in the of Land 6	18 17	16	15	14	13
above were in conformance w Court of Law; established,	ith the rules of the Michigan Bo	ard of Land Surveyors or by a Dec re-monumented, recovered, fo	cree of a 'und as 8	19 20	21	22	23	24
expressed below:  NOTE: Not more than 2 c	orners, all in the same town	n and range, may be recorde	d 10	30 29	28	27	- 26	25
on this certificate			11 - 12	31 32	33	34	35	36
38.84 chains (25 Pine Beec 2. January 22, 1898, He At quarter post S NBT	63,44 feet) Set quarter section  12" S62½°E  S07°W  Sorry M. Caukin, Minutes of Secuthside of section, found old pine stmp 22 S45°E	14 links (9.24 feet) 20 links (13.20 feet) survey Book 2-A Page 55 I stake bottom at only point cla 56½ links (37.29 feet)		20 and .	STATE OF THE PRO	F MIC LLIAM (INGLE) FESSIO	a. WL	**
3. June, 1985, Glen S. Found 5/8" iron r	-lackbardt, # 25844, LCRC Li rod near C/L E-W road and on	line with stump fence south		i c		<b>NO.</b> 30104		ē
Cons NW o	s. Power pole N10°E cor barn S50°E or barn S20°W	34.90 feet 153.90 feet 146.80 feet		· ·	PROF	*******	AL SUPPL	
Searched the apparer Found 5/8" iron pipe below road surface. C. Description of monume Set remonumentation Fnd & set N/T \	nt location of the original co 6" below road surface with Found stump fence south o ent for corner and accessories in pipe over wood post and in W/S power pole N14°E post elec. Panel N72°E barn S27°W	applied in restoring or reestaborner, excavated 2.00 feet x 2 n end of pipe in wood post. f corner. s established to perpetuate locaron pipe, set plow point and 34.97 feet 110.71 feet 153.87 feet 154.03 feet	2.00 feet x 1.50 f	ide of pir of the co ong side BY THE MO THE OFFIC	mer: pipe. NTCALM ( NAL CORI	COUNTY NER UN	/ SURVE	EY PEER CHIGAN
This corner is accented as	s the best available evidenc	e of the position of the origin	nal corner.		William Ti	ngley, PS	, Chairm	ian
Bearings given are magne		ation pipe consists of a Bern		steel 2 3/8	•	• •	-	
Signed by W	an E I	inage Date C	10/26/0	<u>ر</u>				
Surveyor's Michigan Licens	se No. 30104		FORM APPROVED BY	MICHIGAN STA	TE BOARD OF		REVISED MA	