

SURVEY & REMONUMENTATION

L1871 Pg. 647

A1752

APR 04 1996

COMMISSION

LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

<u>Muskegon</u> <small>(County)</small>	Located In:	Corner Code #
1. Public Land Survey	T <u>9N</u> R <u>15W</u>	<u>B-6</u>
	T _____ R _____	
	T _____ R _____	
	T _____ R _____	
2. Property Controlling in Section	S _____ T _____ R _____	
	S _____ T _____ R _____	
3. Miscellaneous Property in Sec.	S _____ T _____ R _____	
	S _____ T _____ R _____	
4. Lot No. _____, Recorded Plat _____		
5. Private Claims _____		

SURVEY & REMONUMENTATION

APR 04 1996

COMMISSION

STATE OF MICHIGAN
COUNTY OF MUSKEGON
RECORDATION DIVISION
MAY 19 1996 PM 4:18

Register of Deeds Stamp & File Number

	A	B	C	D	E	F	G	H	I	J	K	L	M
2	6	5	4	3	2	1							
3													
4	7	8	9	10	11	12							
5													
6	•	17	16	15	14	13							
7													
8	19	20	21	22	23	24							
9													
10	30	29	28	27	26	25							
11													
12	31	32	33	34	35	36							
13													

I, Stephen V. Vallier, P.S., in a field survey on December 8, 1995, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

Corner not set by GLO
1982 CF Lewandowski - found 1/2" Iron Rod at intersection of 1/4 lines. Reset with 4" x 30" Cast Iron Monument. Recorded L.C.R.C. Liber 1242 Page 304.
S 18 deg. W 14.88' 1/2" Iron Rod (nail)
S 83 deg. E 43.83' Power Pole (nail)
S 65 deg. W 45.53' 12" Black Gum Tree (nail)
N 38 deg. W 53.62' 8 - 4" Twin Oak (nail)

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Found 4" x 30" Cast Iron Monument with County Survey Cap.
S 18 deg. W 14.88' 1/2" Iron Rod (nail)
S 83 deg. E 42.83' Power Pole (nail)
S 65 deg. W 45.53' 12" Black Gum Tree (nail)
N 38 deg. W 53.62' 8 - 4" Twin Oak (nail)

POSITION OF SAID RECORDED CORNER REVIEWED & RATIFIED BY MUSKEGON COUNTY PEER GROUP IN ACCORDANCE WITH P.A. 345, OF 1990
Nov 13, 1991

Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Found 4" x 30" Cast Iron Monument with County Survey Cap.
S 18 deg. W 14.88' 1/2" Iron Rod (nail)
S 83 deg. E 42.83' Power Pole (nail)
S 65 deg. W 45.53' 12" Black Gum Tree (nail)
N 38 deg. W 53.62' 8 - 4" Twin Oak (nail)



ed by *Stephen Vallier* Date *Dec 15, 1995*
Surveyor's Michigan License No. 28428