FOR CORNERS OF -: LOCATED IN -:	CORNER CODE NUMBER
I. PUBLIC LAND SURVEY 8 T. 10 XX, R. 16 W.	C-4
2. PROPERTY CONTROLL- ING IN SECTION—,TN. RE.	
PROPERTY IN SECTION, T S., R W.	
4. LOT NO, RECORDED PLAT	
5. PRIVATE CLAIMS	REGISTER OF DEEDS STAMP AND FILING NUMBER
formance with the rules of the Michigan State Board of Regis law:	ed with circles on index code diagram—over) were, in a e-established, monumented, re-monumented, recovered or ons and rules therefore as required in the current manual Interior, Bureau of Land Management or by a decree of a oned in lines 3, 4 and 5 above were, in a field survey on olished or re-established as expressed below and in construction for Land Surveyors or, by a Decree of a Court of
A. Description of original monument and accessories and/or s	subsequent restoration:
B. Description of corner evidence found and/or method applie	d in restoring or re-establishing corner:
Old Witnesses	
NNE, 41.0', 12" Oak	
NW, 110.0', Power Pole	
SE, 18.0', Twin Oak	
C. Description of monument for corner and accessories esta Found 3/4 Pipe 0.5 below surface	blished to perpetuate locating the position of the corner:
S48°E, 17.43', Twin 16" Oak, Pk & tag	
N20°E, 41.00°, 18" Oak, Pk & tag	
N84 E, 49.66, 12" Oak, Pk & tag	,3
	D.I.M.D.
SIGNED BY	
SURVEYOR'S MICHIGAN REGISTRATION NO.	( SEAL )
FOR STATE AND UNITED STATES AGENCIES:	DATE
SIGNED BYCHIEF OF SURVEY PARTY	. 10 January 17, 1974
APPROVED AND SIGNED BY MICHIGAN RECISTERED LAND S	URVEYOR (SEAL)
	· ·•
SURVEYOR'S MICHIGAN REGISTRATION NO. 18655	PROVED BY MICHIGAN STATE BOARD OF REGISTRATION, JAN. 28, 1171

PAGE 3