CORNERS OF -: LOCATED IN -:	CORNER CODE NUMBER	
PUBLIC LAND SURVEY 8 T. 10 N. R. 16 W.		- (60h
		1,11)5/10
PROPERTY CONTROLL- ING IN SECTION——, T. —— S., R. —— W.		- PO C
MISCELLANEOUS PROPERTY IN SECTION, T S., R W.		
LOT NO, RECORDED PLAT		_
PRIVATE CLAIMS		REGISTER OF DEEDS STAMP AND FILING NUMBER
Donald L. Bissell do hereby certicle corner points mentioned in lines 1 and 2 above (ide ald survey on January 3 1974, established stored as expressed below and in conformance with regularity instructions of the United States Department of survey instructions of the United States Department of States Departm	ed, re-established, monu- ulations and rules there the Interior, Bureau of mentioned in lines 3,4 established or re-establ Registration for Land Sc	fore as required in the current mandal. Land Management or by a decree of a and 5 above were, in a field survey or ished as expressed below and in con- inveyors or, by a Decree of a Court o
. Descripcion of organic		
B. Description of corner evidence found and/or method Old Witnesses	applied in restoring or r	e-establishing corner:
Old Witnesses ENE, 94.45', Spike	applied in restoring or r	e-establishing corner:
Old Witnesses	applied in restoring or r	e-establishing corner:
Old Witnesses ENE, 94.45', Spike NW, 66.10', P.P.		
Old Witnesses ENE, 94.45', Spike NW, 66.10', P.P.		
Old Witnesses ENE, 94.45', Spike NW, 66.10', P.P. SW, 40.90', Spike C. ESE, 113.80', Spike C. Description of monument for corner and accessories		
Old Witnesses ENE, 94.45', Spike NW, 66.10', P.P. SW, 40.90', Spike C. ESE, 113.80', Spike C. Description of monument for corner and accessorie Monument box £ Giles Rd.		
Old Witnesses ENE, 94.45', Spike NW, 66.10', P.P. SW, 40.90', Spike C. Description of monument for corner and accessorie Monument box £ Giles Rd. N59°W, 67.93', Power pole, Pk & Tag N71°E, 95.02', Power pole, Pk & Tag	es established to perpetu	
Old Witnesses ENE, 94.45', Spike NW, 66.10', P.P. SW, 40.90', Spike C. Description of monument for corner and accessorie Monument box £ Giles Rd. N59°W, 67.93', Power pole, Pk & Tag	es established to perpetu	
Old Witnesses ENE, 94.45', Spike NW, 66.10', P.P. SW, 40.90', Spike C. Description of monument for corner and accessorie Monument box £ Giles Rd. N59°W, 67.93', Power pole, Pk & Tag N71°E, 95.02', Power pole, Pk & Tag	es established to perpetu	ate locating the position of the come
Old Witnesses ENE, 94.45', Spike NW, 66.10', P.P. SW, 40.90', Spike C. Description of monument for corner and accessorie Monument box £ Giles Rd. N59°W, 67.93', Power pole, Pk & Tag N71°E, 95.02', Power pole, Pk & Tag	es established to perpetu	ate locating the position of the come
Old Witnesses ENE, 94.45', Spike NW, 66.10', P.P. SW, 40.90', Spike C. Description of monument for corner and accessorie Monument box £ Giles Rd. N59°W, 67.93', Power pole, Pk & Tag N71°E, 95.02', Power pole, Pk & Tag S71°E, 109.23', Power anchor pole, Pk	es established to perpetu & Tag	ate locating the position of the come
Old Witnesses ENE, 94.45', Spike NW, 66.10', P.P. SW, 40.90', Spike C. ESE, 113.80', Spike Monument box £ Giles Rd. N59°W, 67.93', Power pole, Pk & Tag N71°E, 95.02', Power pole, Pk & Tag S71°E, 109.23', Power anchor pole, Pk	es established to perpetu & Tag	ate locating the position of the come
Old Witnesses ENE, 94.45', Spike NW, 66.10', P.P. SW, 40.90', Spike C. Description of monument for corner and accessorie Monument box £ Giles Rd. N59°W, 67.93', Power pole, Pk & Tag N71°E, 95.02', Power pole, Pk & Tag S71°E, 109.23', Power anchor pole, Pk SIGNED BY SURVEYOR'S MICHIGAN REGISTRATION NO. FOR STATE AND UNITED STATES AGENCIES:	es established to perpetu & Tag	E (SEAL)
Old Witnesses ENE, 94.45', Spike NW, 66.10', P.P. SW, 40.90', Spike C. ESE, 113.80', Spike C. Description of monument for corner and accessorie Monument box £ Giles Rd. N59°W, 67.93', Power pole, Pk & Tag N71°E, 95.02', Power pole, Pk & Tag S71°E, 109.23', Power anchor pole, Pk SIGNED BY	& Tag DAT	E(SEAL)

PAGE 4