

LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A. 1970

FOR CORNERS OF--	LOCATED IN--	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY <u>S</u>	T. <u>10</u> N. <u>X</u> , R. <u>15</u> W.	<u>B-5, C-5</u>
2. PROPERTY CONTROLLING IN SECTION _____	, T. _____ N. _____, R. _____ E. _____ S. _____, R. _____ W. _____	_____
3. MISCELLANEOUS PROPERTY IN SECTION _____	, T. _____ N. _____, R. _____ E. _____ S. _____, R. _____ W. _____	_____
4. LOT NO. _____, RECORDED PLAT _____		
5. PRIVATE CLAIMS _____		

Miss [unclear]
[unclear]
White Road

REGISTER OF DEEDS STAMP AND FILING NUMBER

I, D. Bissell do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above (identified with circles on index code diagram—over) were, in a field survey on Oct. 1980, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on _____ 19____, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

A. Description of original monument and accessories and/or subsequent restoration:

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

<p><u>B-5</u> Found R.R. Spike 1.5' N. of E. Post. White Road</p>	<p><u>C-5</u> Found 3/8" Iron Pipe 2' North of E Post White Road</p>
---	--

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

<p><u>B-5</u> Rail Road Spike N. 85° E. 50.50' 16" B. Oak N. 57° E. 84.40' 22" B. Oak N. 71° E. 104.31' Power Pole S. 02° E. 73.16' 10-12-14 Trip's B. Oak</p>	<p><u>C-5</u> 3/8" Iron Pipe S. 37° E. 41.69' Transformer Pole N. 55° W. 78.44' 14" Train B. Oak N. 50° E. 48.15' 18" B. Oak N. 21° W. 67.71' 10" W. Oak</p>
--	--

SIGNED BY _____ DATE _____

SURVEYOR'S MICHIGAN REGISTRATION NO. 13255 (SEAL)

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY _____ DATE _____
CHIEF OF SURVEY PARTY

APPROVED AND SIGNED BY _____ DATE _____
MICHIGAN REGISTERED LAND SURVEYOR (SEAL)