		LAND CORNER R	ECORDATION CERT	IFICATE
Fo	r corners in	Filing Requiremen	nt of Act 74, Mich. P	A. 1970
	Marquette Toodheal	Located In:	Corner Code ≠#	
1	Public Land Survey	T	EB	
2		S <u>21.</u> . T R	16	
3	Miscellaneous			Register of Deeds Stamp & File Number
I. do on Cui Ma ab-	Reith Sackett with hereby certify that under requirines 1 and 2 above were in corrent manual of survey instructionagement or by a decree of a Coove were in conformance with truth of Law, established, released below	orded Plat	70. the corner points ments is therefore as required in of the Interior, Bureau of its mentioned in lines 3, 4 d Surveyors or by a Decre nented, recovered, found	2 8 5 4 3 2 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
A	on this certificate. Description of original more	nument and accessories and/or a	subsequent restoration	12 31 32 33 34 34 35 35 36 13 1 1 1 1 1 1 1 1 1 1
Br ac Ki	E8 iginal monument and cessories not found. Found aberly Clark monument set b l kazianka 6-29-67.	F9 Original monument and accessories not found. Found	16 Found Kimberly Cta d set by Ed Kazianka	ark monument

B Description of corner evidence found and/or method applied in restoring or reestablishing corner.

EA	F9	16
Restored at Kimberly Clark monument.	Restored at Kieberly Clark monument.	Restored at Kimberly Clark monument.

C Description of monument for corner and accessories established to perpetuate locating the position of the corner. 16
K.C. sonument 1" 10 by 36"
I.P. with 4" alusinus cap.
5" maple 869E .60ch \$28, BT
6" maple N45E .55ch \$21, BT
8" maple N30W 32.5" 1/16s, BT K.C. sonument 1"10 by 36" L.P. K.C. sonument 1" 10 by 36" mith 4° aluminum cap. 1.P. with 4° aluminum cap. 7° aspen M52M .325ch 620, MBT 12° j. pine N53M 1.79ch 621, 10° aspen NSSE 1.72ch S21, NBT NBT 5" aspen 688W 3.8" 1/4s, NBT 4" aspen 639E 15.6' 1/4s, NBT 4" aspen 639E 15.6' 1/4s, NBT 12" twin r. pine 549N 40.' 1/4s, NBT

Surveyor's Michigan License No.

SKILLL UND SURPETOR NO 19006

REVISEO MAY 14, 1976 REVISEO JAN , 1983