LAND CORNER RECORDATION CERTIFICATE

JOB NOMBER: 93300 SHEET NO. : 1-347	Filing Require	ement of Act 74, Mich. P.A. 1	970
For corners in	9	, , , , , , , , , , , , , , , , , , , ,	· · · · · · · · · · · · · · · · · · ·
1. Public Land Survey 2. Property Controlling S	Located In: 1, T _{47N} R 24W T _{47N} R 25W T R R T R R T R R	Corner Code ##	MARQUEI IN COURT HICHIGAN ECEIVED FOR BUT 33 DEC 29 MI D MARQUEITE OF BUT REGISTER OF BUT RE
in Section S	T R	4 170	_ 1 me 43 ω 3 ₹
	T R		Register of Deeds Stamp & File Number
4. Lot No, Recorde			ABCDEFGHIJKL
5. Private Claims			20 6 5 1 3 - 2 - 1 -
			3 4 7 8 9 10 11 12
I,	mance with regulations and of the United States Departs of Law and/or that the corner les of the Michigan Board of lished, monumented, re-m	d rules therefore as required in the ment of the Interior, Bureau of Land r points mentioned in lines 3, 4 and 5 f Land Surveyors or by a Decree of a nonumented, recovered, found as	5 6 18 17 16 15 14 13 7 8 19 20 21 22 23 24 9 10 30 29 28 27 26 25 11 12 31 32 33 34 35 36
A. Description of original monum	ent and accessories and	l/or subsequent restoration:	13
Section 1, T47N-R25W. 1844: Wi survey notes describe the corn referenced by: 20" Hemlock S55W, 15 1 6" Sugar N22E, 26 1			
B. Description of corner evidence 1993 - Recent surveys of Secti a found 1 1/2 inch iron pipe a of Section 6. The position co above maps aforementioned abov distance to the SW corner of S feet. This distance checks wi 1/16 corner distance shown on Scenic Hills Estates indicatin used in determining that East	ons 6 & 7 have indicated to the W1/4 corner cresponds to the in Part A. The ection 6 is 2622.61 thin 0.52 feet of the the recorded plat of ing that this iron pipe wa	Replaced the found 1 1/2 Survey Monument. Peer gr	
C. Description of monument for c	orner and accessories e	stablished to perpetuate locatin	g the position of the corner:
Marquette County Survey Monume 6° White Birch S43W 23.75 f 15° Spruce N40W 29.30 f 25° White Pine N10W 29.52 f 14° Triple Maple N70E 8.88 f	nt stamped to identify t t. t. t.	eminum pipe capped with a 3 1/4" the corner referenced by nails i	n;
Monument is 0.4 ft. above grou Bk. 4, Pg. 6	nd. Corner falls in wood	ed subdivision therefore no bea	STATE OF MICHIGAN
Signed by Luck U	Contror	_{Date} / Z-23	GERALD W. XV. CARLSON X SURVEYOR X
Signed byU	24589	FORM	APPROVED BY MICHIGAN STATE BOARD APPLYING SURVEYERS NO. 28, 1971

.

Record 347

Part "A" Continued:

An old survey map by R. Washburn, P.S. with no date on it also indicates an iron at the W 1/4 corner of Section 6.

1966 - the recorded plat of Whispering Pines Addition No. 1 indicates some sort of a marker at the W 1/4 corner of Section 6. No accessories were given.