

SURVEY & REMONUMENTATION

Approved by Menominee County
Land Survey Remonumentation
Four Group Under Act 246 of

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

P.A. of 1970 On Dec 16 1994

For corners in
MENOMINEE
(County)

COMMISSION
Located In:

Corner Code #

- | | | | | | | |
|---------------------------------------|---|------------|---|------------|---|-------------|
| 1. Public Land Survey | T | <u>32N</u> | R | <u>27W</u> | | <u>I-09</u> |
| | T | | R | | | |
| | T | | R | | | |
| | T | | R | | | |
| 2. Property Controlling
in Section | S | | T | | R | |
| | S | | T | | R | |
| 3. Miscellaneous
Property in Sec. | S | | T | | R | |
| | S | | T | | R | |
4. Lot No. _____, Recorded Plat _____
5. Private Claims _____

W. Lewis RLS
Chairman
ACTING

RECEIVED FOR RECORD
94 DEC 27 AM 10:48
PAGE # 184 BK 4
BARBARA MORRISON
REGISTER OF DEEDS
MENOMINEE, MI 49850

Register of Deeds Stamp & File Number

William Lenca May 05 1994

I, _____, in a field survey on _____, 19____, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

	A	B	C	D	E	F	G	H	I	J	K	L	M
2	6	5	4	3	2	1							
3													
4	7	8	9	10	11	12							
5													
6	18	17	16	15	14	13							
7													
8	19	20	21	22	23	24							
9													
10	30	29	28	27	26	25							
11													
12	31	32	33	34	35	36							

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

- 1847: Original Survey by James H. Mullett - B.T.'s - Cedar, 10", N41°W, 29 lks; Cedar, 10", S51°E, 34 lks. All original evidence for this corner has been destroyed by Highway Construction.
- 1976: Certified Survey No. 66 by George B. Wilson, RLS No. 17607, indicates that this corner is a chisel hole in pavement (U.S. Highway 41. Measurements are shown to the 1/4 Corner 1/2 mile East and to other corners in the survey.
- 1981: Certified Survey No. 220 by George B. Wilson, RLS No. 17607, shows a subdivision of the SW1/4 of Section 23, T32N-R27W. The map symbol indicates that a 1/2" dia. Iron Rod was set for the corner position.
- 1991: L.C.R.C. No. 917 by Brian Taavola, MDOT Surveyor (RLS No. 21583) states "Found 1/2" Iron Pin 1.5' East of Sta. 148+90 & on C/L joint of 48th Ave. TIES: (MDOT Ref. tag & nail in C/L of object) Power Pole - N65°E - 53.17'; Power Pole - S30°E - 68.87'; Tel. Pole - N35°W - 70.42'; C/L Manhole Cover - S60°W - 56.80'.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

We found a 1/2 inch diameter iron rod and 4 witnesses as described in L.C.R.C. No. 917, in correct position and matching measurements shown in Certified Survey No. 66 and 220. The corner falls in line the centerline of 48th Avenue East - West, and 1.5 feet East of the centerline of U.S. Highway 41. This corner has been used for many surveys over the past 18 years, and is accepted as the best available evidence of the position of the original corner.



C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Accepted 1/2" dia. Iron Pin (did not attempt to excavate in U.S. Highway 41 to place Monument Box):

NE Corner Brick Building	S56°W	116.82 feet	
5/8" x 24" Iron Rod/2" Alum. cap marked WITNESS MARKER	N64°W	95.39 feet	@ 24" dia Spruce
5/8" x 24" Iron Rod/2" Alum. cap marked WITNESS MARKER	S36°E	89.55 feet	@ 6" Twin Maple
Chiseled "+" on cement headwall	N42°E	69.16 feet	

NOTE: All bearings are magnetic bearings. All distances are measured with steel tape. Distances to trees are to nail in side of tree.

Signed by William Lenca Date Dec. 15, 1994
Surveyor's Michigan License No. 26461