

McDon RLS
Chairman

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

MENOMINEE
(County)

Located In: Corner Code #/

33N 27W I-4

Public Land Survey

T ___ R ___
T ___ R ___
T ___ R ___
T ___ R ___

Property Controlling
in Section

S ___ T ___ R ___
S ___ T ___ R ___

Miscellaneous

S ___ T ___ R ___

Property in Sec.

S ___ T ___ R ___

Lot No. _____, Recorded Plat _____

Private Claims _____

William Lenca in a field survey on Mar 09 1995

I hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

Description of original monument and accessories and/or subsequent restoration:

1848: Original Survey by James H. Mullett - B.T.'s - Hemlock, 6", S72°E, 10 lks. S. Maple, 16", N57°W, 15 lks. All original evidence has been destroyed by Highway construction.

1985: L.C.R.C. No. 713 by William Lenca, RLS No. 26461, states that the corner was reestablished on line and midway between the NW and SW Corners of Section 11, T33N-R27W. Set 1/2" x 18" Iron Rod - TIES: W. Birch, 14" - N36°E - 49.85'; W. Birch, 6" - S48°E - 3.87'; W. Ash, 8" - S16°W + 8.24'; Centerline U.S. "41" - West - 69.90'.

Description of corner evidence found and/or method applied in restoring or reestablishing corner:

We found a 1/2" x 18" Iron Rod/ID cap as described in L.C.R.C. No. 713 in good condition. All 3 White Birch B.T.'s are gone. The corner falls 70 feet East of the centerline of U.S. Highway 41. We accepted the position of the 1/2" diameter iron rod as a careful and faithful reestablishment of the position of the original corner.



Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Set 2" dia. Aluminum Pipe/3-1/4" dia. Alum cap stamped for corner location:

5/8" x 24" Iron Rod/2" dia. Alum. cap marked "Witness Marker"	N12°W	137.72 feet	
7" dia. Cedar	S06°E	83.48 feet	Scr. NBT
15" dia. White Pine (West of Highway)	N70°W	129.00 feet	Scr. NBT
Survey Sign Post	East	1.1 feet	

NOTE: All bearings are magnetic bearings. All distances are measured with EDM. Distances to trees are to nail in side of tree.

Signed by William Lenca Date Apr. 11, 1995
Surveyor's Michigan License No. 26461

	A	B	C	D	E	F	G	H	I	J	K	L	M
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		

RECEIVED FOR RECORDING
95 NOV - 8 11:11:29
PAGE # 213 BK 4
DATE OF RECORDING
MICHIGAN STATE BOARD OF LAND SURVEYORS
RECORDS SECTION
LANSING, MICHIGAN 48906

Register of Deeds Stamp & File Number