

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

Menominee
(County)

Located In: _____ Corner Code ~~##~~ _____

1. Public Land Survey T _____ R _____
 T _____ R _____
 T _____ R _____

2. Property Controlling S 12 T 34N R 26W 1, 2.
 in Section S _____ T _____ R _____

3. Miscellaneous S _____ T _____ R _____
 Property in Sec. S _____ T _____ R _____

4. Lot No. _____, Recorded Plat _____

5. Private Claims _____

Register of Deeds Stamp & File Number

I, David B. Babbitt, in a field survey on 8/17/87, 19____, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

	A	B	C	D	E	F	G	H	I	J	K	L	M
2	6	5	4	3	2	1							
3													
4	7	8	9	10	11	12							
5													
6	18	17	16	15	14	13							
7													
8	19	20	21	22	23	24							
9													
10	30	29	28	27	26	25							
11													
12	31	32	33	34	35	36							
13													

A. Description of original monument and accessories and/or subsequent restoration:

1. West 1/16 corner on the north section line of Section 12. No previous record.
2. E 1/16 corner on the north section line of Section 12. No previous record.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

1. Set MPOL between the north 1/4 corner and the NW section corner of Section 12.
2. Set MPOL between the north 1/4 corner and the NE section corner of Section 12.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

- | | |
|----------------------------|----------------------|
| 1. DNR Monument | 2. DNR Monument |
| 5" sugar maple N50E, 28.4' | 7" cedar N33W, 24.6' |
| 4" sugar maple S40E, 46.2' | 10" cedar N8W, 35.6' |
| 4" sugar maple S43W, 38.2' | 5" b.ash N43E, 58.0' |
| 8" beech N32W, 48.9' | 9" cedar S40E, 75.0' |

Signed by David B. Babbitt Date 12-3-87
 Surveyor's Michigan License No. 21558