

FEB 11 1998

Approved by Menominee County
Land Survey Re-monumentation
Pur. Enamp Under Act 345 Of
P.A. Of 1990 Co. 10/31 199 97
McLennan's RLS
Chairman

SECTION

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

MENOMINEE (County)	Located In:	Corner Code #
1. Public Land Survey	T6N R 24W	E-03
	T R	
	T R	
	T R	
2. Property Controlling in Section	S T R	
	S T R	
3. Miscellaneous Property in Sec.	S T R	
	S T R	

REGISTERED FOR RECORD
97 NOV 21 PM 3:17
PAGE 517 RLS
MICHIGAN BOARD OF PROFESSIONAL SURVEYORS
REGISTERED FOR RECORD

Register of Deeds Stamp & File Number

4. Lot No. _____, Recorded Plat _____
5. Private Claims _____

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6		5		4		3		2		1		
3					3								
4	7		8		9		10		11		12		
5													
6	10		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

William Lchca, in a field survey on Aug. 25, 1997 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and for that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below.

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

- A. Description of original monument and accessories and/or subsequent restoration:
- 1848: Original Survey by James H. Mullett - B.T.'s - Cedar, 10" - S43°W - 18 lks.; Cedar, 10" - S80°E - 19 lks. All original evidence for this corner has been destroyed by county road improvements.
 - 1968: L.C.R.C. No. 563 (Vol. 3) recorded by Frank Bray: Set 1-1/4" x 30" Iron Pipe in gravel road from NBT's used by MSHD. Witnesses: 16" Aspen - N22°W - 28.94'; 8" Cedar - S25°E - 42.68'.
 - 1979: CERTIFIED SURVEY No. 153 by George B. Wilson, RLS No. 17607: Shows a subdivision of Section 4, T36N-R24W. The SW Corner is described as a "Pin".

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

We recovered a 1/2 inch diameter iron rod with plastic identification cap marked RLS 17607. The corner was found in the centerline of an East - West County Road, at a distance West of the S1/4 Corner of Section 4 which matches with Wilson's record distance shown in Certified Survey No. 153. The position of the pin also matched well with the stump of an Aspen - N22°W - 28.94 feet, but was 1' long of matching the Cedar B.T. - S25°E - 42.68 feet. Since the present corner position has been accepted and used by local surveyor's for 18 years, we accepted the position of the found iron pin as the best available evidence of the position of the original corner.

- C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:
Set 2" dia. Aluminum Pipe 30" long/3-1/4" dia. Alum cap stamped for corner location:
- | | | | |
|------------------------|-------|------------|----------|
| 10" dia. Blue Spruce | N30°E | 29.81 feet | Scr. NBT |
| 9" dia. Cedar | S25°E | 43.46 feet | Scr. NBT |
| 16" dia. White Spruce | S54°W | 56.66 feet | Scr. NBT |
| 6" dia. Balsam | N45°W | 44.52 feet | Scr. NBT |
| Metal Survey Sign Post | North | 19.2 feet | |

NOTE: All bearings are magnetic bearings. All distances are measured with steel tape. Distances to trees are to nail in side of tree.

Signed by William Lchca Date Aug. 28, 1997
Surveyor's Michigan License No. 26461