

LAND CORNER RECORDATION CERTIFICATE
 Filing Requirement of Act 74, Mich. P.A. 1970 as Amended

For corners in

<u>Menominee</u> (County)	Located In:	Corner Code #
1. Public Land Survey	T _____ R _____ T _____ R _____ T _____ R _____	_____
2. Property Controlling in Section	S <u>28</u> T <u>36N</u> R <u>25W</u> S <u>28</u> T <u>36N</u> R <u>25W</u> S _____ T _____ R _____	POL E of 13 POL E of 13 _____
3. Miscellaneous Property in Sec.	S _____ T _____ R _____ S _____ T _____ R _____	_____ _____
4. Lot No. _____, Recorded Plat _____		
5. Private Claims _____		

Register of Deeds Stamp & File Number

1	A	B	C	D	E	F	G	H	I	J	K	L	M
2		6		5		4		3		2		1	
3													
4		7		8		9		10		11		12	
5													
6		18		17		16		15		14		13	
7													
8		19		20		21		22		23		24	
9													
10		30		29		28		27		26		25	
11													
12		31		32		33		34		35		36	
13													

I, Jeremy J. Pipp, in a field survey on 1/10/2012AD do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

(POL) Point on the South One-Sixteenth Line of Section 28. Not set in original survey, no evidence of subsequent establishment.

(POL) Point on the South One-Sixteenth Line of Section 28. Not set in original survey, no evidence of subsequent establishment.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

(POL) Point on South One-Sixteenth Line of Section 28, lying 15 feet West of the Top of Bank of the Cedar River.

(POL) Point on South One-Sixteenth Line of Section 28, lying 9 feet East of the Top of Bank of the Cedar River.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

(POL) 1" Pipe with Plastic Cap
 7" Ash S13E 14.68' (POL,BT)
 8" White Pine N75W 37.17' (POL,BT)
 All trees are blazed, scribed, and painted. Measurements are to nail in side of tree, bearings are magnetic.

(POL) 1" Pipe with Plastic Cap
 6" Maple N78E 6.45' (POL,BT)
 8" White Pine S12E 21.40' (POL,BT)
 All trees are blazed, scribed, and painted. Measurements are to nail in side of tree, bearings are magnetic.

Signed by Jeremy J. Pipp
 Surveyor's Michigan License No. 50447



Date July 16, 2012

20016
20017