

MICHIGAN  
DEPARTMENT OF CONSERVATION  
FORESTRY DIVISION

LAND CORNER RECORD

T.36.. NR..28.W..

Menominee COUNTY

DESCRIPTION OF CORNER Section Corner common to Sec.'s 28-29-32-33

DESCRIPTION OF CORNER MONUMENT Found  $2\frac{1}{2}$ " pipe with  $3\frac{1}{2}$ " brass cap set by Wisc.-Mich. Power Co. and  $3/4$ " iron bar set by J. C. Lymer, Surveyor in 1927.

WITNESSES TO CORNER Found new witnesses as follows:

2" W. Pine S  $77^{\circ}$  E 29 links

scribed "BT"

12" Red Oak S  $75^{\circ}$  W 16 links

scribed "BT"

9" W. Pine N  $12^{\circ}$  W  $5\frac{1}{2}$  links

scribed "BT"

These trees marked several years ago by Wisc.-Mich. Power Co.

DESCRIPTION IN DETAIL AS TO HOW CORNER WAS LOCATED AND IDENTIFIED OR RESTORED.

Corner lies 4 chs. north of road.

Possible B.T. is 24" W. Pine stump S  $40^{\circ}$  E 34 links.

SURVEYORS SEAL

SIGNED

*Billy D. Buckler*  
REGISTERED LAND SURVEYOR

DATE 4/16/57